

10-02-00

A

Docket No.: 50275-0014

UTILITY PATENT APPLICATION
UNDER 37 CFR 1.53(b)

Box PATENT APPLICATION
Assistant Commissioner for Patents
Washington, DC 20231
Sir:

Transmitted herewith for filing is the patent application of:

INVENTOR: CHRISTOPHE PIERRAT, YOUPIING ZHANG
FOR: PROXIMITY MODEL DISSECTION FOR PROJECTION POINTS

Enclosed are:

- ☒ 74 pages of specification, claims, abstract.
- ☒ Declaration and Power of Attorney.
- ☐ Priority Claimed.
- ☐ Certified copy of _____
- ☒ 20 sheets of informal drawing.
- ☒ An assignment of the invention to Numerical Technologies, Inc.
and the assignment recordation fee.
- ☒ Assignment Recordation Sheet.
- ☐ Information Disclosure Statement, Form PTO-1449 and reference.
- ☒ Verified Statement (Declaration) Claiming Small Entity Status)
- ☒ Return Receipt Postcard

The filing fee has been calculated as shown below:

	NO. OF CLAIMS		EXTRA CLAIMS	RATE	AMOUNT
Total Claims	63	-20	43	\$18.00	\$774.00
Independent Claims	27	-3	24	\$78.00	\$1,872.00
Multiple Dependent Claim(s)					\$0.00
Basic Fee					\$690.00
Total of Above Calculations					\$3,336.00
Less 1/2 for Small Entity					\$1,668.00
Assignment & Recording Fee					\$40.00
Total Fee					\$1,708.00

09/29/00
JC836 U.S. PTO


JC836 U.S. PTO
09/675197
09/29/00

09/29/00
JC836 U.S. PTO

- ☒ Enclosed is a check in the amount of \$1,708.00. A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 50-1302. A duplicate copy is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 50-1302. A duplicate copy of this sheet is enclosed.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Respectfully submitted,

HICKMAN PALERMO TRUONG & BECKER, LLP



Brian D. Hickman
Registration No. 35,894

1600 Willow Street
San Jose, CA 95125-5106
(408) 414-1080 BDH:sj
Date: September 29, 2000
Facsimile: (408) 414-1076

EXPRESS MAIL CERTIFICATE OF MAILING

"Express Mail" mailing label number EL624353851US Date of Deposit _____

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Box: New App Fee, Assistant Commissioner for Patents, Washington, D.C. 20231.

Susan J. Johnson
(Typed or printed name of person mailing paper or fee)

[Signature]
(Signature of person mailing paper or fee)

Applicant or Patentee: Christophe Pierrat and Youping Zhang Attorney's Docket No.: 50275-0014
Serial or Patent No.: _____
Filed or Issued: Herewith
For: PROXIMITY MODEL DISSECTION FOR PROJECTION POINTS

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
(37) CFR 1.9(f) and 1.27(c) - SMALL BUSINESS CONCERN

I hereby declare that I am
☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF ORGANIZATION: NUMERICAL TECHNOLOGIES, INC.
ADDRESS OF ORGANIZATION: 70 West Plumeria Drive, San Jose, California 95134-2134

I hereby declare that the above identified small business concern qualified as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, oral third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled PROXIMITY MODEL DISSECTION FOR PROJECTION POINTS by inventor(s) CHRISTOPHE PIERRAT and YOUPING ZHANG described in

☒ the specification filed herewith;
☐ application Serial No. _____, filed _____,
☐ patent no. _____, issued _____.

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who could not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e). *NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME _____
ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION
NAME _____
ADDRESS _____
☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING: RICH MORA
TITLE IN ORGANIZATION: CFO
ADDRESS OF PERSON SIGNING: 70 West Plumeria Drive, San Jose, California 95134-2134
SIGNATURE: [Signature]
DATE: 9/29/06

50275-0014

Patent

UNITED STATES PATENT APPLICATION

FOR

DISSECTION OF EDGES WITH PROJECTION POINTS
IN A FABRICATION LAYOUT
FOR CORRECTING PROXIMITY EFFECTS

INVENTORS:

CHRISTOPHE PIERRAT
YOUPIING ZHANG

Prepared by:

Hickman Palermo Truong & Becker, LLP
1600 Willow Street
San Jose, California 95125
(408) 414-1080

EXPRESS MAIL CERTIFICATE OF MAILING

"Express Mail" mailing label number EL624353851US

Date of Deposit September 29, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Gugan J. Johnson
(Typed or printed name of person mailing paper or fee)

[Signature]
(Signature of person mailing paper or fee)

DISSECTION OF EDGES WITH PROJECTION POINTS IN A FABRICATION LAYOUT
FOR CORRECTING PROXIMITY EFFECTS

5

RELATED APPLICATIONS

This application is related to U.S. patent application serial number _____
(Attorney Docket 50275-0013), entitled "Dissection Of Corners In A Fabrication Layout For
Correcting Proximity Effects," filed on September 29, 2000, invented by Christophe Pierrat
and Youping Zhang.

10

This application is related to U.S. patent application serial number _____
(Attorney Docket 50275-0015), entitled "Dissection Of Printed Edges From A Fabrication
Layout For Correcting Proximity Effects," filed on September 29, 2000, invented by
Christophe Pierrat and Youping Zhang.

15

This application is related to U.S. patent application serial number _____
(Attorney Docket 50275-0016), entitled "Selection Of Evaluation Point Locations Based on
Proximity Effects Model Amplitudes For Correcting Proximity Effects In A Fabrication
Layout," filed on September 29, 2000, invented by Christophe Pierrat and Youping Zhang.

20

This application is related to U.S. patent application serial number _____
(Attorney Docket 50275-0017), entitled "Displacing Edge Segments On A Fabrication
Layout Based on Proximity Effects Model Amplitudes For Correcting Proximity Effects,"
filed on _____, invented by Christophe Pierrat and Youping Zhang.

BACKGROUND OF THE INVENTION

The Field of the Invention

5 This invention relates to the field of printed feature manufacturing, such as integrated circuit manufacturing. In particular, this invention relates to automatically identifying evaluation points where errors are computed and analyzed to achieve improved agreement between a design layout and an actual printed feature.

10 Description of Related Art

 To fabricate an integrated circuit (IC), engineers first use a logical electronic design automation (EDA) tool, also called a functional EDA tool, to create a schematic design, such as a schematic circuit design consisting of symbols representing individual devices coupled
15 together to perform a certain function or set of functions. Such tools are available from CADENCE DESIGN SYSTEMS and from SYNOPSYS. The schematic design must be translated into a representation of the actual physical arrangement of materials upon completion, called a design layout. The design layout uses a physical EDA tool, such as those available from CADENCE and AVANT!. If materials must be arranged in multiple
20 layers, as is typical for an IC, the design layout includes several design layers.

 After the arrangement of materials by layer is designed, a fabrication process is used to actually form material on each layer. That process includes a photo-lithographic process using a mask having opaque and transparent regions that causes light to fall on photosensitive material in a desired pattern. After light is shined through the mask onto the photosensitive
25 material, the light-sensitive material is subjected to a developing process to remove those portions exposed to light (or, alternatively, remove those portions not exposed to light). Etching, deposition, diffusion, or some other material altering process is then performed on the patterned layer until a particular material is formed with the desired pattern in the

particular layer. The result of the process is some arrangement of material in each of one or more layers, here called printed features layers.

Because of the characteristics of light in photolithographic equipment, and because of the properties of the material altering processes employed, the pattern of transparent and opaque areas on the mask is not the same as the pattern of materials on the printed layer. A mask design process is used, therefore, after the physical EDA process and before the fabrication process, to generate one or more mask layouts that differ from the design layers. When formed into one or more masks and used in a set of photolithographic processes and material altering processes, these mask layouts produce a printed features layer as close as possible to the design layer.

The particular size of a feature that a design calls for is the feature's critical dimension. The resolution for the fabrication process corresponds to the minimum sized feature that the photolithographic process and the material processes can repeatably form on a substrate, such as a silicon wafer. As the critical dimensions of the features on the design layers become smaller and approach the resolution of the fabrication process, the consistency between the mask and the printed features layer is significantly reduced. Specifically, it is observed that differences in the pattern of printed features from the mask depend upon the size and shape of the features on the mask and the proximity of the features to one another on the mask. Such differences are called proximity effects.

Some causes of proximity effects are optical proximity effects, such as diffraction of light through the apertures of the optical systems and the patterns of circuits that resemble optical gratings. Optical proximity effects also include underexposure of concave corners (inside corners with interior angles greater than 180 degrees) and overexposure of convex corners (outside corners with interior angles less than 180 degrees), where the polygon

represents opaque regions, and different exposures of small features compared to large features projected from the same mask. Other causes of proximity effects are non-optical proximity effects, such as sensitivity of feature size and shape to angle of attack from etching plasmas or deposition by sputtering during the material altering processes, which cause features to have shapes and sizes that have decayed from or accumulated onto their designed shapes and sizes.

In attempts to compensate for proximity effects, the mask layouts can be modified. To illustrate, Figure 1A shows mask items 170, such as windows or opaque areas on a mask, represented by edges 171 on one or more polygons, and some printed features 180 with exaggerated proximity effects. Figure 1A does not represent an actual example, but is provided simply to illustrate the concepts of proximity effects and mask modifications to attempt to correct for proximity effects. To make apparent the illustrated proximity effects, the projection of the original polygons 171 is shown as a fine line around the printed features 180. Note that the printed features 180 includes a spurious connection feature 182, an edge 185 entirely displaced inside the corresponding edge of the original outline 171, and an end line 183 completely inside the outline of the original items 171.

Figure 1B illustrates various ways mask items 190 are modified to correct for such effects. Figure 1B is not a particular example of a particular set of corrections that actually mitigate the proximity effects illustrated in Figure 1A. The corrections available include hammerheads 192 added to ends of items to compensate for overexposure of the entire end line of a feature. Also shown are biases 196 applied along portions of a straight edge of a feature. A negative bias like 196 represents a portion of an opaque area made transparent (or a portion of a window made opaque). In this case the negative bias reduces the size of the item on a mask to avoid generating the spurious feature 182 of Figure 1A. Also shown are

assist features 194, which are separate items smaller than the resolution of the photolithographic process and thus too small to be formed in a photoresist layer, but which are sufficiently large to effect diffraction patterns that influence larger nearby features. The assist features 194 are intended to move the edge 185 of the printed features 180 in Figure 1A toward the outline 171 of the original mask items 170. Also shown is a sub-resolution serif 193 of extra opaque material to compensate for overexposure at convex corners of opaque areas, and an anti-serif 197 indicating where opaque material, if any, is removed to compensate for underexposure at concave corners of opaque polygons. These corrections are listed to illustrate the concepts of correcting a mask to compensate for proximity effects. The illustrated corrections do not necessarily correct the depicted features.

In rule-based proximity corrections, corrections such as the serifs and biases of a predetermined size are automatically placed at corners and edges of fabrication layout shapes like the mask shapes 170. Other rules may include adding assist shapes to a mask near desired features from the design layout and adding hammerheads to short end lines of the desired features. Experience of engineers accumulated through trial and error can be expressed as rules, and applied during the fabrication design process. For example, a rule may be expressed as follows: if a feature is isolated, then widen the opaque region in the mask by a particular amount to compensate for expected overexposure, so that the feature prints properly.

The experience captured in rule-based corrections is garnered by going through the fabrication process repeatedly with different mask layouts, making adjustments and observing the results. However, this process consumes time and manufacturing capacity. Even if such experimental, rule-forming runs are made, the resulting rules often do not give

satisfactory results as the features become more complicated, or become smaller, or interact in more confined areas, or involve any combination of these effects.

Because rule based corrections are often imprecise and time consuming to revise and test, a proximity effects model is often developed and used to predict the effects of a change in the mask layout with more precision and with fewer off line fabrication runs.

A proximity effects model is typically built for a particular suite of equipment and equipment settings assembled to perform the fabrication process. The model is often built by performing the fabrication process one or a few times with test patterns on one or more mask layouts, observing the actual features printed (for example with a scanning electron micrograph), and fitting a set of equations or matrix transformations that most nearly reproduce the locations of edges of features actually printed as output when the test pattern is provided as input. The output of the proximity effects model is often expressed as an optical intensity. Other proximity effects models provide a calibrated output that includes a variable threshold as well as an optical intensity. Some proximity effects models provide a calibrated output which indicates a printed edge location relative to a particular optical intensity as a spatial deviation. Thus some model outputs can take on values that vary practically continuously between some minimum value and some maximum value.

Once a proximity effects model is produced, it can be used in the fabrication design process. For example, the proximity effects model is run with a proposed mask layout to produce a predicted printed features layer. The predicted printed features layer is compared to the design layer and the differences are analyzed. Based on the differences, modifications to the proposed mask layout are made, such as by adding or removing serifs 193, or adding or removing anti-serifs 197. After making these corrections to the proposed mask layout, a final mask layout is generated that is used in the fabrication process.

A proximity effects model typically produces predictions that lead to corrections that are more accurate than rule based corrections. However, a proximity effects model consumes computational resources by an amount that is related to the number of points of interest where amplitudes are computed. For typical mask layouts, the number of points where the model could be run is large, and the computation time is prohibitive. Therefore it is typical to run the proximity effects model at selected evaluation points located on the edges of features, to determine the correction needed, if any, at each evaluation point, and then to apply that correction to all the points on a segment of the edge in the vicinity of the evaluation point.

If too many evaluation points are selected, the model runs too slowly and the correction procedure takes too long. If too few evaluation points are selected, the model may not detect critical locations where corrections are necessary. Another undesirable effect of too few evaluation points is that segments can become too large, so that even if a correction is accurate for the evaluation point, the correction is applied to too much of the edge. This causes undesirable changes on the edge away from the evaluation point.

What are needed are new ways to select evaluation points and define their vicinity for the mask layouts, so that a reasonable number of comparisons can be made and so that effective modifications to the mask layouts can be suggested.

SUMMARY OF THE INVENTION

According to techniques of the present invention, edges of polygons in a mask layout are dissected into segments defined by dissection points, with each segment having an evaluation point, according to modified dissection rules. These techniques allow the spacing of evaluation points and dissection points to be automatically adapted to portions of each edge where changes in the proposed mask layout are most likely needed. According to these techniques, dissection points are closer together where proximity effects are more significant and are farther apart where proximity effects are less significant. Thus unnecessary evaluation points are eliminated and the analysis process is speeded up, while still retaining needed evaluation points.

In one aspect of these techniques, all dissection points can be derived from just a few easily defined parameters. The first parameter is a corner dissection segment length, L_{cor} , used as a target length to compute dissection points for corner segments that include at least one vertex of the polygon when the length of the edge allows. The second parameter is a detail dissection segment length, L_{det} , used as a target length to derive dissection points for segments along portions of an edge where changes in proximity effects are expected to be significant, such as adjacent to corner segments and around projection points when the length of the edge allows. A projection point is a location on an edge where a vertex of another edge comes close enough to introduce sharp changes in the proximity effects. A halo distance is a parameter that determines whether a vertex is close enough to introduce an important effect. A maximum dissection segment length, L_{max} , by definition larger than either L_{cor} or L_{det} , is used as a target length to further dissect long portions of the edge that would otherwise not be dissected, such as away from corners and projections points. Extra precision is achieved if a true-gate extension length parameter L_{ext} is used on edges of shifters forming true-gates. The dissection parameters L_{cor} , L_{det} , L_{max} , halo and L_{ext} are pre-set and accessed as needed.

In one aspect of the disclosed techniques, a profile of amplitudes from a proximity effects model along an edge of a feature in a design layout is used to dissect the edge. This amplitude profile reflects the level of proximity effects for the given layout and fabrication process. By using this information, a better dissection of the edge is achieved in which the segment length between successive dissection points depends on the magnitude of the proximity effects. For example, on a portion of an edge where the magnitude of the proximity effects is larger than another portion, the segment length is made longer. This kind of dissection avoids making the segment length too short. A segment that is too short, for example in a corner, may result in a very large correction, and may prevent the overall corrections for the layout from converging.

In another aspect, the dissection parameters are derived from the segment lengths based on profiles of amplitudes. According to the modified dissection rules, each evaluation point is placed along a segment at a predetermined fraction of the distance from one dissection point to the other defining each segment, where the predetermined fraction depends on the type of segment. For example, an evaluation point is placed closer to the non-vertex dissection point in a corner segment; and is placed midway between dissection points in other types of segments. Also according to the modified dissection rules, segments are located on polygon edges according to the type of edge, such as whether the edge is a line end, a turn end, or a longer edge. These edge types are deduced from the length of the edge compared to the dissection parameters and whether one or both vertices of the edge are concave or convex corners.

Specifically, according to some aspects of the invention, techniques for correcting proximity effects in a proposed layout corresponding to a design layout for a printed features layer include selecting from among all edges of all polygons in the proposed layout a subset of edges for which proximity corrections are desirable. The subset of edges includes less than all the edges. Evaluation points are established only for the subset of edges.

Corrections are determined for at least portions of the subset of edges based on an analysis performed at the evaluation points.

According to other aspects, techniques for correcting proximity effects associated with an edge corresponding to a design layout include establishing a projection point on a first edge corresponding to the design layout based on whether a vertex of a second edge corresponding to the design layout is within a halo distance. The halo distance is associated with significant proximity effects on one edge from a vertex of another edge. The first edge is divided into segments based on the projection point and characteristics of the first edge. It is then determined how to correct the first edge for proximity effects based on the segments.

According to other aspects, techniques for correcting proximity effects associated with an edge corresponding to a design layout include establishing a projection point on a first edge. An evaluation point is determined for the first edge based on the projection point and characteristics of the first edge. It is then determined how to correct at least a portion of the edge for proximity effects based on an analysis at the evaluation point.

According to one embodiment of this aspect of the invention, if the vertex of the second edge is within the halo distance of the first edge, then establishing a projection point includes placing the projection point on the first edge closest to the vertex.

According to another embodiment of this aspect of the invention, determining the evaluation point includes establishing on the first edge two evaluation points spaced apart at least by a target length for detail segments. The two evaluation points straddle the projection point.

According to another embodiment of this aspect of the invention, before establishing a projection point, the halo distance is determined. This includes executing a proximity effects model at several points along a test edge to produce a profile of model amplitudes. A variation in amplitude is determined that is associated with a test vertex on a different test edge. A distance between the test edge and the test vertex is associated with the variation in amplitude. The proximity model is run, the variation is determined, and the distance is

associated with the variation for several test edges. Then the halo distance is set based on a distribution of distances associated with variations for the test edges.

According to another embodiment of this aspect of the invention, a computer system for correcting proximity effects associated with an edge corresponding to a design layout includes a computer readable medium carrying data representing the edge, the halo distance, and at least a portion of the design layout. The design layout corresponds to a portion of an integrated circuit. One or more processors are coupled to the computer readable medium. The processors are configured to perform the following steps. A projection point is established on a first edge corresponding to the design layout based on whether a vertex of a second edge is within the halo distance. An evaluation point for the first edge is determined based on the projection point and characteristics of the first edge. A proximity effects model is executed for the evaluation point to produce a model amplitude. A correction is determined for at least a portion of the first edge including the evaluation point based on an analysis of the model amplitude. The correction is then applied to that portion of the first edge.

According to another embodiment of this aspect of the invention, a device is fabricating using a mask for fabricating a printed features layer that includes an opaque region having a segment corrected for proximity effects. The segment corresponds to at least one portion of a first edge in a design layer for the printed features layer. The segment is displaced from the corresponding portion in the design layer by a correction distance. The correction distance is based on analysis of an amplitude output by a proximity effects model at an evaluation point on the corresponding portion. The evaluation point is based on a projection point and characteristics of the edge. The projection point is established based on whether a vertex of a second edge corresponding to the design layout is within the halo distance of the first edge.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings and in which like reference numerals refer to similar elements and in which:

5 Figure 1A is a plan view of two items on a mask and the resulting printed features showing proximity effects.

 Figure 1B is a plan view of elements on a modified mask after adjusting the mask of Figure 1A in an attempt to correct for proximity effects.

10 Figure 2 is a flow chart showing the sequence of processes and layouts utilized in the formation of devices having printed features layers according to one embodiment of the disclosed techniques.

 Figure 3 is a flow chart of a process for selecting dissection points according to one embodiment.

15 Figure 4A is a plan view of elements on a mask used as input to an illustrative proximity effects model.

 Figure 4B is a plan view illustrating printed features with proximity effects that might result from the mask items of Figure 4A superposed on an ideal projection of the mask items.

20 Figure 4C is a graph of contours of constant model amplitude output on a two dimensional array resulting from the input of Figure 4A for the exemplary proximity effects model.

 Figure 4D is a graph of a profile of model amplitude along a line shown in Figure 4C for the exemplary proximity effects model.

 Figure 5A is a plan view of elements on a second mask layout used as input to a second proximity effects model.

Figure 5B is a graph of a profile of model amplitude along an edge of a polygon from Figure 5A.

Figure 5C is a graph of a first derivative of the profile of Figure 6B showing dissection points according to one embodiment.

5 Figure 5D is a graph of a second derivative of the profile of Figure 6B showing dissection points according to another embodiment.

Figure 6 shows an exemplary test pattern for a fabrication process, a profile location, and the corresponding exemplary model output along the profile.

10 Figure 7 is a flow diagram for setting dissection parameters according to one embodiment.

Figures 8A-8E are partial plan views of polygons from mask layouts showing placement of dissection points and evaluation points according to one embodiment.

Figure 9 is a flow diagram for selecting dissection points using the dissection parameters according to one embodiment.

15 Figures 10A through 10C are partial plan views of overlapping polygons from two mask layouts, showing the placement of dissection points and evaluation points when not all of a polygon is printed, according to several embodiments.

Figure 11 is a flow diagram of a process employed when changing edges for selecting dissection points and evaluation points according to one embodiment.

20 Figure 12 is a block model of a computer system configured according to one embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Techniques are described for correcting fabrication layouts for proximity effects during the fabrication of printed features layers, such as in integrated circuits.

FUNCTIONAL OVERVIEW

5 Figure 2 shows the processes and layouts produced according to the present techniques for designing and fabricating printed features layers 249 for devices 250. The conventional processes are modified to include new techniques for selecting evaluation and dissection points, as represented in Figure 2 by process 260.

10 The conventional processes include the Functional EDA process 210 that produces the schematic diagram 215. The physical EDA process 220 converts the schematic diagram to a design layout made up of one or more design layers 225. After mask layouts 235 are produced, the conventional processes employ a fabrication process 240 to produce the printed features layer 249. The printed features layer 249 may be a layer in a printed circuit or the mask used to produce the layer in the printed circuit. In the former case, the
15 fabrication process includes one process 243 for forming the mask and a second process 245 to produce the layer of the integrated circuit using the mask. If the printed features layer 249 is the mask, step 245 is skipped.

 According to techniques of the present invention, the fabrication design process 230 includes a new process 260 for obtaining dissection and evaluation points. In one
20 embodiment, these new dissection and evaluation points are determined for a proposed mask layout 231 and used with a proximity effects model in step 232 to produce a model output 233. The model output is related to the predicted location of edges in the printed features layer if a printed features layer were fabricated with a mask having the proposed mask layout. Hence, in Figure 2, the model output is called the predicted printed features edge.

Each evaluation point is established for a segment of an edge from the proposed mask layout. The segment is defined by a pair of dissection points associated with the evaluation point. Once the dissection points and evaluation points are selected, the proximity effects model is run at the evaluation points. . In step 234, the predicted printed features edge 233 for the evaluation point is compared to a target position for that edge in the design layer. Based on an analysis of the comparison, a correction distance is computed. The correction distance is then applied to the entire segment between dissection points associated with the evaluation point on the edge of the affected polygon. As each correction is applied, the mask layout is adjusted in step 236. As a result of the adjustments in step 236 the polygons on the adjusted mask layout may differ from the polygons in the proposed mask layout, as well as from the polygons in the design layers 225. The final mask layouts 235 are then based on the adjusted mask layouts produced by the adjustment process 236.

OBTAINING DISSECTION AND EVALUATION POINTS

An overview of one embodiment for the new dissection/evaluation points selection process 260 is illustrated in Figure 3. According to this embodiment, a few dissection parameters are established in response to predictions from a proximity effects model in step 310. In another embodiment, a human operator sets the dissection parameters. Those few dissection parameters represent the necessity of dissection along varying portions of various types of edges. These parameters are used to select all the dissection points and evaluation points on an edge of a polygon of a fabrication layout in step 330. In step 370, an evaluation point is placed on each segment defined by a pair of successive dissection points on the edge. The process then continues over all the edges needing dissection, on all the polygons in the layout.

For example, in step 390, it is determined whether the current edge is the last edge on the current polygon. If not, process flow passes to step 392 where the next edge requiring dissection on the polygon is selected and made the current edge. Flow then returns to step 330 in which the edge newly made current is dissected according to the dissection parameters. If the edge just processed by steps 330 and 370 is the last edge of the current polygon, process flow passes to step 394 in which it is determined whether the current polygon is the last one needing dissection in the fabrication layout. If not, the next polygon is made the current polygon in step 396, and control passes to step 392 in which the first edge needing dissection on the polygon is made the current edge. If the current polygon is the last on the layout then flow passes to step 232 of Figure 2, where the proximity effects model is run at the selected evaluation points.

In an alternative embodiment, step 394 includes making another fabrication layout the current fabrication layout and then passing control to step 396. Such a subsequent layout may be necessary to dissect; for example, when the two fabrication layouts are used to doubly expose the same printed features layer, so that edges from the second fabrication layer become part of the printed features layer. This circumstance will be described in more detail later below.

EXAMPLES OF SELECTING DISSECTION/EVALUATION POINTS & SETTING DISSECTION PARAMETERS USING A PROXIMITY EFFECTS MODEL

According to one embodiment, the proximity effects model is used to set the dissection parameters, for example, in step 310. These parameters remain constant during the dissection of several polygons in step 330, on one or more proposed fabrication layouts during the fabrication layout design process, step 230.

Herein the term amplitude is used to describe the proximity effects model output associated with a location no matter what model is used. In general, the models are built to accept input representing polygons of opaque or transparent material. In general, an amplitude value is then produced for each location of interest. A threshold amplitude
5 between the minimum amplitude value and the maximum amplitude value can be associated with the model. As used here, the threshold amplitude is associated with the location where the edge of a feature is actually printed. For example, where spatial deviation is output by the model, a threshold of zero marks the location of an edge. As another example, where the model output is simple optical intensity, a non-zero positive value associated with the printed
10 edge serves as the threshold. In some models, the threshold value associated with an edge may itself be a function of several variables such as the optical intensity and intensity gradient at a location.

To understand how dissection parameters can be derived from proximity effects model output, consider Figures 4 and 5.

15 Figure 4A shows two items 410 and 420 represented by polygons 411 and 421, respectively, in a mask layout provided as input to a proximity effects model that has been developed for a particular suite of equipment and settings. Figure 4B shows the printed features 412 and 422, with shapes 413 and 423, respectively, that would be produced from a mask formed from the mask layout of Figure 4A according to the proximity effects model.

20 For reference, Figure 4B also shows the polygons 411 and 421 if those were projected perfectly onto the printed features layer. The differences between the ideal and actually printed features are due to proximity effects. For example, arrow 415 shows the deviation of printed feature 413 from the design layout polygon 411 at one location on the polygon 411. Similarly, arrow 425 shows the deviation of printed feature 423 from the design layout

005250 " 6752950
polygon 421 at a location on that polygon 421. These deviations are output by one kind of proximity effects model.

Figure 4C illustrates contours 450 of constant amplitude on a two dimensional array of model output for one kind of proximity effects model, if it were to be run for every point on such an array. One particular contour representing the threshold value, contour 450c, is shown as a bold line. The shapes formed by the bold contour 450c represent this model's prediction of the shape of the printed features accounting for all proximity effects in the system. As can be seen by the bold contour 450c in Figure 4C, this proximity effects model predicts printed features with shapes that agree with those that actually would be produced on the printed features layer, as shown in Figure 4B.

For simplicity of explanation, the proximity effects model that outputs contours like those shown in Figure 4C is used as an exemplary proximity effects model in the rest of this specification, unless otherwise stated. The techniques of the present invention, however, work with any proximity effects model, including those models which have been calibrated to produce amplitudes representing the predicted printed feature

Figure 4C also shows a double arrow 460 along which a profile of model amplitude is plotted in Figure 4D. In Figure 4D, model amplitude is expressed in arbitrary units on the vertical axis 484 from zero to a maximum represented by a value of 1.0. Distance along the double arrow of Figure 4C from left to right is shown on the horizontal axis 482 of Figure 4D, in arbitrary distance units. Along this profile the model amplitude begins at zero, rises steadily from about 3 distance units to about 5 distance units, flattens out to about 7 units, then dips at about 8 units, rises to a peak at about 9 distance units, and then falls off to zero again at about 13 distance units.

The threshold value 470 of about 0.3 model amplitude units corresponds to the value of contour 450c. Where the model output is above the threshold value 470, a feature is predicted to be printed in the printed features layer; where the model output is below the threshold value 470, no feature is predicted to be printed. Where the model output equals the threshold value is where the edge of the printed feature is predicted to lie. Of course model output units are arbitrary and could be inversely related to what is printed, so that low amplitudes represent printed features and high amplitudes represent no printing. In such a case, the threshold would mark the value below which a feature is printed.

The selection of dissection points and the derivation of dissection parameters from a profile of model output is illustrated in Figures 5A, 5B, 5C and 5D.

Figure 5A is a plan view of elements on a second mask layout used as input to another proximity effects model. The mask elements include two transparent items, 510 and 520, represented by a first polygon with edges 511 through 516 and a second polygon with edges 521 through 524, respectively. On the polygon of item 510, points 532 and 533 indicate where proximity effects are expected to vary sharply because of the corner point 538 between edges 514 and 515. Also shown are points 531, 534, 535 and 536 on the polygon of item 510 where proximity effects are expected due to the corner between edges 521 and 522 of the polygon of item 520. Points 531 through 536 are projection points, where proximity effects on one edge are expected to vary sharply because of the proximity of vertices of other edges.

A profile of model amplitudes along one of these edges reflects the size of proximity effects on that edge for this particular layout and model (where the model represents this particular suite of fabrication equipment and settings). By using information in this profile of

amplitudes, a better dissection of this edge can be performed in which the segment length depends on the proximity effect magnitude.

Figure 5B is a graph of a profile 540 of model amplitude along edge 511 of the polygon of item 510 shown in Figure 5A, from its vertex in common with edge 516 to its vertex in common with edge 512. For purposes of illustration, the threshold for this model is taken as 0.23. This model then predicts that this edge 511 will print from about 100 nanometers (nm) to about 1100 nm. Arrow 541 indicates the location of projection point 531 and the value of amplitude at that projection point. Curve 543 indicates where the amplitude curve 540 would be expected to lie if there were no variation in proximity effects on edge 511 due to item 520. Arrow 542 indicates the location of projection point 532 and its amplitude. Curve 544 indicates where the amplitude profile 540 would be expected to lie if there were no variation in proximity effects on edge 511 due to corner point 538. As expected, the proximity effects represented by curve 540 vary in the vicinity of the projection points.

This profile 540 is used to illustrate how particular dissection points are selected on this edge, as well as how the dissection parameters used for dissecting other edges are derived from model output on this edge, according to this embodiment. In other embodiments, variations on the techniques described here are used.

This profile 540 illustrates a length scale of proximity effects at corners of a polygon. That corner length scale is found from a vertex of the edge to a position where the profile flattens near amplitude 0.3. That length scale is about 200 nm. In an alternative embodiment, the corner length scale is selected to be the distance to the threshold value of 0.23, which is about 150 nm. In still another embodiment, the corner length scale is taken to be a distance to an amplitude that is a given percentage of the threshold value. In this case,

the given percentage is selected based on how aggressive a correction is sought in the vicinity of corners. Where more aggressive correction is desired, the percentage is chosen to be less than 100%. Where less aggressive correction is desired, the percentage is chosen to be greater than 100%. In still other embodiments, the corner length scale is associated with types of corners, e.g., concave or convex, or angle at the corner, or both. The corner length scale so derived provides a target length to use when dissecting corners where the edge allows.

This profile also suggests a length scale for details near projection points.

Considering both sides of each projection point, that detail length scale should be about half the distance over which curve 540 deviates from curves 543 and 544. That detail length scale is about 100 nm. The detail length scale so derived provides a target length to use when dissecting details where the edge allows. This profile also suggests a maximum length scale where the curve 540 hardly varies at all, between the two projection points, of about 300 nm. The maximum length scale so derived provides a target length to use when dissecting edges away from corners and details, where the edge allows.

Along other edges, the distances for the amplitude curve to flatten, the distances over which projection points have noticeable effects, and the length of the undisturbed sections are expected to vary. Thus, dissection parameters based on these must be derived from the observed distributions of length scales. In a preferred embodiment, instead of using a single corner scale from one polygon of one test layout, a statistical corner scale, such as an average corner scale, or median corner scale, is used as a dissection parameter near corners. The statistical corner scale is derived from the corner segment lengths of several polygons on the same test layout or on several layouts. In other embodiments, different corner scales are derived for different corner types, e.g., concave or convex, or different ranges of angles or

both. For example, corner segments associated with acute angles less than 45 degrees can be averaged separately from corner segments associated with intermediate angles from 45 through 80 degrees which themselves are averaged separately from corner segments associated with nearly right angles from 80 to 100 degrees.

5 In another model where proximity effects are different, the values of the length scales and their distributions are also expected to be different. For example, in an equipment suite with lower resolution optics and material processes, the length parameters are expected to be larger. That is, a distance from a vertex of an edge to a flattening point is expected to be greater for all edges tested, and, therefore, the derived dissection parameter is expected to be larger.

10 In one embodiment, an evaluation point for a corner segment is determined on this curve. According to this embodiment, the evaluation point is placed where the curve has a value equal to a given percentage of the amplitude value where the curve first flattens. For example, if the given percentage is set at 75%, then because curve 540 flattens at about 0.31 amplitude units, the evaluation point is selected where the curve has a value of 75% of 0.31, i.e., a value of .23. This occurs at a distance of about 100 nm. In another embodiment, the evaluation point is placed where the profile has a value equal to a given percentage of the threshold value, e.g., 90% of the threshold value of 0.23, which is 0.21. This occurs at about 90 nm on curve 543.

15 20 The following paragraphs define particular embodiments for determining dissection points and length scales for dissection parameters. Other embodiments rely on variations of these techniques known in the art.

Figure 5C is a graph of a curve 550 representing a first derivative of the profile 540 of Figure 5B. The first derivative is a measure of the slope of the profile 540 at each point

along the profile. Where the profile 540 flattens the slope 550 approaches zero. A particular small value of slope, say .001, is chosen to indicate where a profile is flat. A profile is flat where the absolute value of its first derivative is less than this particular value. Starting from a distance of 0 nm, the curve 550 first becomes less than this particular value at about 200 nm. According to this embodiment, a corner segment is placed on this edge from 0 nm to 200 nm where the first derivative decreases to the particular value. The corner segment is marked by dissection points located at the vertex at 0 nm and at about 200 nm.

The 200 nm length of this corner segment is then submitted to a process to derive a corner dissection segment length parameter, Lcor. That process performs a weighted average of this corner length for this edge with other corner lengths from this and other edges to derive the corner dissection segment length, Lcor. In one embodiment, the weights are all the same.

Similarly, moving along edge 511 from its vertex in common with edge 512, at a distance of 1200 nm, the slope first increases above -.001 at about 1000 nm. That is, the absolute value of the first derivative decreases below the particular value of 0.001 at about 1000 nm. This indicates a corner segment for this edge lies from distance 1000 nm to 1200 nm, and dissection points are placed at both those locations. As above, the 200 nm corner segment length is submitted to the process to derive the corner dissection segment length dissection parameter, Lcor.

Figure 5C also shows arrows 551 and 552, which indicate the locations of projection points 531 and 532, respectively. Though the absolute value of slope at 551 may exceed the particular value of .001, this does not appear to be the case at 552. The slope near the projection point at 552 appears to be affected by the opposite slope associated with the corner segment. Along curve 550, the absolute value of the slope exceeds the particular value of

.001 also near points indicated by arrows 553 and 554, at about 300 nm and 860 nm, respectively.

According to this embodiment, dissection points are added at each location where the absolute value of slope reaches a local maximum above the small particular value. One embodiment adds dissection points at 553, 551 and 554, which are located at about 300 nm, 480 nm and 860 nm, respectively. Thus, segments that extend from 200 to 300 nm, 300 to 480 nm, and 860 to 1000 nm are added to the two corner segments already defined for this particular edge 511. A residual edge that undergoes further dissection remains between points 551 and 554, from about 480 to 860 nm. Evaluation points are then placed on this edge, one evaluation point on each segment. In this embodiment, each evaluation point is placed midway between the dissection points on each non-corner segment.

The non-corner segment lengths obtained from these embodiments are sent to a process to derive other dissection parameters, such as a detail dissection segment length, L_{det} , and a maximum dissection segment length, L_{max} . In one embodiment of the process to derive dissection parameters, a histogram of segment lengths is formed and the detail dissection segment length, L_{det} , is derived from a mode of the distribution associated with the smallest lengths. In this embodiment, a maximum dissection segment length is derived from a second mode associated with the next smallest lengths. In other embodiments, length scales may be derived from such a distribution of lengths using any methods known in the art. Then, dissection parameters are set based on the derived length scales.

In another embodiment of selecting dissection points from model output along a particular edge, dissection points are also added between these local slope maxima, either at a midpoint, or where the slopes are interpolated to closest approach zero. This embodiment will tend to produce twice the number of segments and cause the dissection parameters

derived from the resulting segments to have about half the size. Evaluation points are then placed at the midpoints of the resulting segments.

In still another embodiment, dissection points are added at non-adjacent points where the slope curve 550 has a slope whose absolute value equals the particular minimum slope value, e.g., 0.001. This embodiment adds two dissection points for each local maximum such as at 553 and 554, one on either side of each local maximum.

In another embodiment, before adding dissection points, the second derivative of the profile 540 is computed and examined. Figure 5D is a graph of a curve 560 representing a second derivative of the profile 540 of Figure 5B. The second derivative measures the curvature of a profile. A positive value indicates that the profile is turning about a center above the profile, while a negative value indicates the profile is turning about a center below the profile. A zero indicates an inflection point where the profile is not curved. Arrows 561 and 562 indicate the locations of projection points 531 and 532, respectively.

Both projection points are located near points where curve 560 crosses zero. In this embodiment, dissection points are added wherever the second derivative is interpolated to cross zero. This method can be used even for corner segments if the crossing of zero closest to the corner is ignored. Using this method, one corner segment extends from 0 nm to the point indicated by arrow 565, at about 220 nm, and a second corner extends from the point at arrow 568, at about 990 nm to 1200 nm. These lengths of 220 nm and 210 nm, respectively, are sent to a process to derive a corner dissection segment length, L_{cor} .

This technique also produces dissection points as indicated by arrows 563 at about 320 nm, 561 (associated with projection point 531) at about 480 nm, 566 at about 760 nm, and 564 at about 880 nm. These points yield non-corner segments of lengths 100 nm, 160 nm, 280 nm, 120 nm, and 110 nm. These lengths are sent to the process for deriving non-

corner dissection parameters, and support a detail dissection segment length L_{det} of about 110 nm, and a maximum dissection segment length L_{max} of about 300 nm.

According to one embodiment, an evaluation point is placed at the point on each segment where the absolute value of the second derivative is a maximum. For example,
5 evaluation points are placed at 100 nm, 300 nm, 400 nm, 800 nm, 950 nm, and 900 nm, where the second derivative curve 560 reaches local extreme values between locations where the curve 560 crosses zero.

Using these example embodiments, a proximity effects model is run for a variety of locations along one or more edges of one or more polygons. The polygons can be selected
10 from a proposed or final mask layout, or from a design layer of a design layout, or from a test mask used to build the proximity effects model. The profile of model output along the edge is used to select dissection points and evaluation points for that particular edge. The resulting segment lengths for the particular edge are used with segment lengths obtained for other edges to derive target lengths to use as dissection parameters.

15 This technique allows the proximity effects model to be run at a few locations, i.e., along certain edges, rather than at every point in a layout. Certain important edges are dissected directly, and the remaining edges are dissected using the dissection parameters. The proximity effects model is then run for all other edges only at the evaluation points. Thus a large number of model runs are avoided and the computation proceeds at a desirable
20 rate. At the same time, the evaluation points are reasonably selected to give the necessary detail on all the edges.

DERIVING DISSECTION PARAMETERS FROM A TEST MASK

The profiles such as 640 can be generated by any method known in the art. In one embodiment, the test patterns used to build the model are used. These test patterns already include a range of features at different scales and model output computed on a relatively dense output grid. Thus with substantially no additional computations than those already made to build the proximity effects model in the first place, model amplitudes along various polygon edges are already available for deriving dissection parameters.

In another embodiment, the corner length scale is derived from the model output at a series of features of varying pitch. Pitch refers to the smallest distance between repeated features in a layer. The use of features of varying pitch to derive a length scale appropriate for a given model is shown in Figure 6.

Figure 6 shows an exemplary test pattern 692 of elongated polygons for a suite of fabrication equipment. Figure 6 also shows a profile location 695, and the corresponding exemplary model 690 amplitudes along the profile. The pitch associated with portion 692a of the test pattern 692 is illustrated by the separation 691a. Similarly, portions 692b, 692c and 692d have associated pitches 691b, 691c and 691d, respectively, of ever increasing size. The section 695 is perpendicular to the elongated polygons. The profile 690 on the section shows a portion 690a in which model output never exceeds the threshold amplitude 470 associated with a feature being printed. Thus this portion of the test pattern is too closely spaced to be printed with the equipment suite modeled by the proximity effects model. Portion 690b of profile 690 does cross the threshold amplitude, barely. Other portions 690c and 690d cross substantially above the threshold. In this example, the particular pitch 691b associated with profile portion 690b, represent a transition from unprintable to printable scales. Feature lengths smaller than this particular scale are not likely to have different

printable effects. Consequently, dissecting features into segments smaller than this scale will likely generate too many segments and too many evaluation points. It is expected that corrections for such segments will not converge on a solution appropriate for the entire layout. If profile portion 690b had been entirely below the threshold, then a length scale
5 representing the transition from unprintable to printable scales is obtained by interpolating to a pitch at the threshold amplitude on a plot of maximum amplitude versus pitch.

In one embodiment, the particular pitch length scale associated with maximum model output at the threshold value is used to set a corner dissection segment length. In another embodiment, this particular pitch length scale is used to set a detail dissection segment
10 length.

METHOD FOR DERIVING DISSECTION PARAMETERS

Figure 7 is a flow diagram for setting dissection parameters according to one embodiment of the present invention. This is one embodiment of step 310a for setting dissection parameters based on a proximity effects model output.

15 In step 710, a profile of proximity effects model amplitudes is generated along at least one edge of a polygon on a test layout. In the preferred embodiment, the test pattern is one used to generate the proximity effects model. In another embodiment, the polygon can be selected on-the fly from a proposed fabrication layout for an actual printed features layer.

In step 730, a corner dissection segment length parameter, L_{cor} , is set to a distance
20 scale representing the distance from a corner, i.e., a vertex of the polygon defining the current edge, to a point on the profile where the profile flattens. The profile is flat, for example, where successive points undergo less than a certain change in amplitude or absolute value of the slope is less than a particular minimum value. In other embodiments, L_{cor} is set to a distance scale representing the distance from the corner to a particular percentage of the

flat portion, or a particular portion of the threshold, or where the second derivative crosses zero. In some embodiments, a set of Lcor parameters are defined, one for each corner type or angle range or both, and set to appropriate distance scales.

In step 750, dissection points are selected away from the corners, defining non-corner segments, based on changes in model output, such as based on the first derivative or second derivative of the model amplitude profile. This step can also be used to define a halo distance, i.e., a separation between features beyond which no dissection points are necessary on an edge. With a halo distance so defined, if some vertex of another edge is within the halo distance of a non-corner segment of the edge whose profile is being examined, a dissection point should be necessary.

In step 770, the detail dissection segment length parameter, Ldet, is based on the segment lengths of the non-corner segments. For example, the detail dissection segment length is set equal to a mode in the distribution of non-corner segment lengths associated with the shortest segment lengths. For a second example, the detail dissection segment length is set to a particular percentile of non-corner segment lengths, such as the 5th percentile length or 10th percentile length.

In step 790, the maximum dissection segment length parameter, Lmax, is based on the segment lengths of the non-corner segments that are substantially longer than the detail dissection segment length. For example, the maximum dissection segment length is set equal to a second mode in the distribution of non-corner segment lengths, a mode not associated with the shortest segment lengths. For a second example, the detail dissection segment length is set to a particular percentile of non-corner segment lengths, such as the 25th percentile length, the 50th percentile length (the median segment length), or the 75th percentile length.

When the halo and dissection lengths are defined, then control passes to step 330 to use these parameters to dissect polygons in an actual fabrication layout.

MODIFIED SELECTION OF DISSECTION AND EVALUATION POINTS

In one embodiment, dissection points are based on the vertices of the polygon and

5 five prescribed dissection parameters. The five prescribed dissection parameters include:

- corner segment dissection length (L_{cor});
- detail segment dissection length (L_{det});
- maximum segment dissection length (L_{max});
- true-gate extension length (L_{ext}); and
- 10 • halo distance (halo).

The vertices and dissection parameters are first used to determine an edge type. Edges shorter than the shortest prescribed segment length are not worth evaluating and so have no dissection points or evaluation points selected. Edges long compared to twice the corner segment length have a dissection point placed about L_{cor} from each vertex. A projection point is located on an edge at the closest point to a vertex of another edge, if that vertex is within the halo distance. Long portions of edges away from the corners and without projection points, i.e., residual edges, may be dissected to prevent segments longer than L_{max} . Next to corner segments and near projection points, segments should be about L_{det} long. Edges of true-gates have lengths increased by the true-gate extension length, L_{ext} , to prevent underexposure of these important features.

In other embodiments, multiple versions of these parameters are defined. For example several L_{cor} parameters are defined to distinguish convex from concave corners and to distinguish square corners from acute and middle angle corners. As another example,

several Lext parameters are defined to distinguish extensions toward an end cap from extensions toward a connector, explained below.

One use of prescribed dissection parameters Lcor and Ldet is illustrated in Figure 8A.

Figure 8A is a plan view of a vertex 811a of a polygon where two edges long compared to

5 Lcor and Ldet meet. The vertex 811a is selected as a dissection point 830a. On the horizontal edge, the next selected dissection point 830b is a distance Lcor 820 from the vertex 811a. Dissection points 830a and 830b define a corner segment. The first segment next to the corner segment has a length Ldet 822, which causes the dissection point 830c to be selected. Similarly, on the vertical edge, the first dissection point 830a is the vertex 811a, and the next selected dissection point 830d is a distance Lcor 820 from the vertex 811a, while the next dissection point 830e is a distance Ldet from there.

There is one evaluation point 840 between each pair of dissection points on an edge.

Away from the corner segments, the evaluation points are placed substantially halfway between the dissection points. For example, evaluation point 840b is halfway between its associated dissection points 830b and 830c. This is done because the evaluation point represents the whole segment between the dissection points; and any correction computed for the evaluation point, such as moving the edge x distance units outward, will be applied to the whole segment. Treating the whole segment together is reasonable because the corrections needed are expected to vary slowly along a single segment. That is how the segment length parameters were chosen – to represent a distance associated with each substantial change in proximity effects.

In the corner segments of this embodiment, however, the evaluation points are not halfway. Instead, in this embodiment, the evaluation point is placed two-thirds (2/3) of the way from the convex vertex to the next dissection point. In other embodiments, the

evaluation point is placed substantially more than halfway from the vertex to the next dissection point. The placement of evaluation points farther from the vertex is reasonable because the proximity effects in the corner tend to increase more rapidly as the corner is approached. Halfway from the corner the changes are still large compared to the inside dissection point which abuts the next segment. A smaller correction is desired than at the halfway point to avoid big differences with the abutting interior segment.

Figure 8A illustrates the use of two of the prescribed dissection parameters. In addition to the segments with lengths substantially equal to the prescribed parameters, this embodiment includes some segments which have lengths which depend on the prescribed parameters but vary from them by an amount determined by the actual length of an edge between successive vertices of the polygon. The derived lengths include

- Effective line-end segment length (d_{min});
- Effective turn-end corner segment length (d_{cor}); and
- Effective interior, flat segment length (d_{max}).

Line-end segments occur on polygon edges that are no shorter than the shortest prescribed segment length but not long enough to generate more than one segment. Line-ends are likely underexposed or overexposed along their entire length. Such edges are not dissected further but do have an evaluation point. Thus on such edges, the dissection points are the vertices and the evaluation point is placed midway between. The segment and the edge are coincident. Though controlled by the prescribed dissection parameters, the actual segment lengths, d_{min} , are derived from the vertex positions. Figure 8B illustrates a line-end edge of polygon 810b. Dissection points 830f and 830g are placed at vertices and evaluation point 840e is placed midway between them. The segment has a length d_{min} 824 derived from the distance between the vertices. Because d_{min} is greater than the lesser of prescribed

parameters L_{det} and L_{cor} , but shorter than $(L_{det} + 2 * L_{cor})$, this edge is treated as a line-end and is given segment length d_{min} substantially equal to its edge length, L . Not shown is a line end comprising two concave vertices. It is treated the same way as the depicted line end with two convex vertices. An edge characterized as a line-end is never dissected into two segments.

Turn-end edges are also longer than the shortest prescribed length but involve one concave vertex and one convex vertex, such as shown in Figure 8C. Thus a turn-end often involves an underexposed corner 811d and an overexposed corner 811e. In addition, a turn-end involves two corners so close together that there is not enough distance for a segment of length L_{det} between them. That is, edge length L 826 is less than $(L_{det} + 2 * L_{cor})$. Such an edge is unlikely to have a properly exposed segment. Depending on the actual length of a turn-end edge, L 826, it gets either a single evaluation point at its midpoint with both vertices being dissection points, or it is split evenly by three dissection points 830 h, 830i and 830k into two segments of length d_{cor} 827, as shown in Figure 8C. Though its segment length is controlled by the prescribed dissection parameters L_{cor} and L_{det} , its actual segment length, d_{cor} 827, is derived from the positions of the vertices and their edge length L 826. In the embodiment shown in Figure 8C, the evaluation points 840f and 840g are placed in the middle of both segments. In another embodiment, at least one segment is considered a corner segment with an evaluation point more than halfway from a corner to the middle dissection point 830i.

Corner, line-end and turn-end dissection lengths are used in those circumstances even if projection points are also present. Projection points control segment lengths in the interior portions of an edge away from the vertices, as will be described later below. Away from corner segments (including all of short edges like line-ends and turn-ends) and projection

points, residual portions of an edge are divided evenly so that no segment is greater than L_{max} and no segment is shorter than the shorter of L_{cor} and L_{det} . Though controlled by the prescribed dissection parameters L_{cor} , L_{det} and L_{max} , the actual length of these segments (d_{max}) is derived from the original vertex positions.

5 Line-end segments occur on polygon edges that are no shorter than the shortest prescribed segment length but not long enough to generate more than one segment. Line-ends are likely underexposed or overexposed along their entire length. Such edges are not dissected further but do have an evaluation point. Thus on such edges, the dissection points are the vertices and the evaluation point is placed midway between. The segment and the
10 edge are coincident. Though controlled by the prescribed dissection parameters, the actual segment lengths, d_{min} , are derived from the vertex positions. Figure 8B illustrates a line-end edge of polygon 810b. Dissection points 830f and 830g are placed at vertices and evaluation point 840e is placed midway between them. The segment has a length d_{min} 824 derived from the distance between the vertices. Because d_{min} is greater than the lesser of prescribed
15 parameters L_{det} and L_{cor} , but shorter than $(L_{det} + 2 * L_{cor})$, this edge is treated as a line-end and is given segment length d_{min} substantially equal to its edge length, L . Not shown is a line end comprising two concave vertices. It is treated the same way as the depicted line end with two convex vertices. An edge characterized as a line-end is never dissected into two segments.

20 Dissection due to a projection point is illustrated in Figure 8E. In this embodiment, the halo distance 855 is used to determine whether any vertex from another edge is within range to induce a sharp change in proximity effect on the current edge. For example, vertex 811f of polygon 810f is within halo distance 855 of the current edge of polygon 810e being dissected. A projection point is defined, as the closest point on the edge from a vertex of

another edge within the halo distance 855. In the preferred embodiment, the halo is defined based on analyzing model amplitudes along an edge on a test pattern as described above.

The model radius is the greatest distance at which the model can display an effect, e.g., the length scale of the longest kernel function used in the model. The halo distance is found in

5 this embodiment, by first selecting a particular variation in proximity effect considered significant. Then the halo distance is set substantially equal to the greatest separation between an edge and a vertex of another edge that exhibits the particular variation or more in the test patterns. In another embodiment, a distribution of observed variations is generated, and the particular significant variation is determined from a certain percentile of these
10 variations, e.g., the 10th percentile. The halo distance can also be defined manually. In this embodiment, the halo distance is preferably defined to be less than or equal to the model radius, e.g., by a pre-defined percentage less than 100% to multiply by the model radius

In Figure 8E, a line 853, parallel to the current edge of the polygon 810e and spaced the halo distance 855 apart, marks the area in which a vertex of another edge can cause a
15 projection point. Since vertex 811f of another edge is within the halo distance, a projection point 850 is found.

In the preferred embodiment, dissection in the vicinity of the projection point is carried out by placing a dissection point 830q at the projection point 850 and at two other points 840r and 840s spaced Ldet 822 from the projection point 850. Evaluation points are
20 then placed at the midpoint of the segments so defined. In another embodiment, an evaluation point is placed at the projection point, and two dissection points spaced Ldet from each other straddle the evaluation point. Such an embodiment is not preferred because it does not allow for different corrections on either side of the projection point as needed for most circumstances, for example, as needed for curve 540 in Figure 5B. In yet another

embodiment, the segment centered on the projection point of this previous embodiment is augmented with two additional segments of length L_{det} , one each on either side of the first segment. While such an arrangement allows for different corrections near to and on either side of the projection point, it requires three evaluations rather than the two evaluations of the preferred embodiment.

Where more than one projection point are initially found on an edge within a distance of L_{det} along the edge, only one projection point is kept and used for dissection. Any technique that provides a single projection point from the multiple initial projection points can be used. According to this embodiment, the projection point kept is the one having the shortest distance to the vertex of another edge. After this one is selected, all other projection points on the edge within L_{det} of the kept projection point are discarded.

Figures 9A and 9B illustrate one embodiment for step 330 of Figure 3, dissecting an edge using the dissection parameters, which combines all the above considerations.

In step 910 of Figure 9A the edge length L is determined from the vertices of the current edge. In step 912 it is determined whether the edge length is less than the minimum dissection length, e.g., the lesser of the corner dissection segment length L_{cor} and the detail dissection segment length L_{det} . If so, the edge is too short to merit an evaluation point and the edge is discarded, i.e., not dissected and not given an evaluation point. Control then passes to step 390 of Figure 3 to obtain the next edge for dissection, if any.

In step 914 it is determined whether the edge length L , which is necessarily greater than or equal to the minimum dissection length, is also less than double the minimum dissection length. If so, then the edge is a line-end or turn end that is treated as a single segment. Dissection points are selected at the vertices in step 915. Control then control passes to step 370 to select an evaluation point, e.g., in the middle of the edge.

In step 916, the edge length L is necessarily greater than double the minimum dissection length, and it is determined whether the edge is long enough to accommodate two corner segments of length L_{cor} and an intervening segment of length L_{det} . If not, the edge is treated as a line end or as a turn-end. In step 918 it is determined whether the edge is a turn end, i.e., includes both a convex corner and a concave vertex. If not, the edge is a line end and dissection points are placed at the two vertices in step 915 and control passes to step 370 to place the evaluation point. If one vertex is a convex vertex and the other is a concave vertex, so that the edge is a turn-end, it is determined in step 920 whether the edge length L is less than double L_{det} . If not, then the edge is split evenly into two segments with dissection points at both vertices and at the mid-point of the edge. If the edge length L is less than double L_{det} , then the edge is kept as one segment with dissection points at the vertices in step 915. In either case, control then passes to step 370 to select evaluation points.

If it is determined in step 916 that the edge length is long enough, two corner segments are placed on the edge, by selecting both vertices of the polygon as dissection points as well as selecting the two points spaced away from the two vertices by the distance L_{cor} . A residual edge length is computed by subtracting double the corner dissection segment length, i.e., subtracting $2 * L_{cor}$, from the edge length L .

In step 930, one or more projection points are selected on the residual edge, for example, as shown in Figure 8E. If more than one projection point is found, only projection points spaced at least L_{det} from another projection point are kept.

In step 940 of Figure 9B, every pair of dissection points not involving a corner segment, such as dissection points related to a projection point or segment adjacent to a corner segment, is examined and a residual length LR of a further residual edge is computed as the distance between the currently examined pair of points. When no more such pairs of

points are left on the edge, flow control eventually passes to step 370 to select evaluation points.

In step 942 it is determined whether the residual length LR is less than twice L_{det} . If so, the segment is not further dissected in step 943, and control passes to step 950 to examine the next such pair of dissection points, unless it is determined in step 951 that the current pair is the last pair and control passes to step 370 in Figure 3. Otherwise control passes to step 944.

In step 944 the residual length LR is necessarily greater than or equal to double L_{det} , and it is determined whether the residual length LR is also less than triple L_{det} . If so, the segment is split evenly into two segments by adding a dissection point in the midpoint of the segment. If not, control passes to step 946.

In step 946 the residual length is necessarily greater than or equal to triple L_{det} , and two dissection points are added, each L_{det} from one of the current pair of dissection points being examined. Then a new residual edge length is computed for the remaining segment between the two new dissection points. Control then passes to step 948.

In step 948, the new residual edge length is divided by L_{max} , and the ceiling integer N of the quotient is obtained. The effective length of the remaining segments, d_{max} , is computed as the residual length divided by the ceiling integer N . By dividing the residual length by the ceiling integer, d_{max} is guaranteed to be less than or equal to L_{max} . Then $N-1$ evenly spaced dissection points, spaced apart by d_{max} , are selected in the remaining segment. Control then passes to step 951 to obtain the next such pair of dissection points in 950 unless the current pair is the last pair and control passes to step 370 in Figure 3.

In one embodiment dissection points and evaluation points are also chosen to be at grid points of a predefined input grid. This additional choice provides the advantage that

previously computed model runs can be used for analyzing differences after the edges get dissected.

SPECIFICALLY SEGMENTING CERTAIN EDGES

In yet another embodiment, the proximity effects model is run for closely spaced points along certain critical edges on a proposed layout or layouts, as described above with respect to Figure 5. Based on the rates of change of model amplitude along the edge, such as the first and second derivative, the edge is divided into segments. For example, a segment is formed for every change in model amplitude along the edge above a predetermined minimum change. For another example, a segment is defined between every inflection point where the second derivative crosses zero. These segments are not derived from the dissection parameters, but are directly observed on the certain edges. Dissection points are then placed at the segment endpoints and an evaluation point is placed between each pair of dissection points.

This embodiment offers the advantage of customizing the dissection for certain important edges and responding to the actual variations in proximity effects observed along the particular edge.

However, this embodiment requires more computational resources than using dissection parameters because the model is run at many new points along an edge in the fabrication layout for the actual design. This embodiment does not use the pre-computed model values created when the model was built.

Some computation time and power is saved compared to running evaluations at all points on these edges, because a correction is only computed at the more widely spaced evaluation points, one per segment. Once computed, the same correction is then applied to the whole segment. Additional computational time and power can be saved by performing

the process only on certain edges expected to suffer from proximity effects, like those on critical features in the layout with dimensions close to the resolution of the fabrication process, or where critical dimensions are within a halo distance of another polygon. For example, this process is used only on edges that include an edge of a true-gate or an edge of a true-gate interconnect.

INCLUDING EDGES FROM DOUBLE EXPOSURES

Some features on a printed layer are formed by exposing the same layer with masks formed according to two fabrication layouts. For example, in a first exposure, narrow phase-shifted features are formed, then, in a second exposure, wider connections between phase-shifted features are formed. Polygons in the first exposure include pairs of phase-shift windows called shifters, which pass light of the same wavelength but out of phase by 180 degrees (or π radians).

Figure 10A illustrates two rectangular shifters 1010a and 1010b that form a true-gate 1001 along a portion of the area between the shifters 1010. For example, shifter 1010a is bounded by four edges connecting vertices 1031, 1036, 1037 and 1038. Also shown is a polygon 1020 used in a second exposure to connect the true-gate 1001a to other features, not shown, with connecting features 1009a and 1009b. Edges connecting vertices 1040, 1043, 1045, 1046, 1047 and 1048 are on polygon 1020. The polygon 1020 includes wide trim sections 1024 entirely within the shifters 1010 where there is no material on the layer being exposed the second time. The purpose of the trim sections 1024 is to prevent overexposing the edge of the true-gate 1001 during the second exposure. The edges of the trim sections 1024 inside the shifters 1010 do not leave edges on the printed features layer. For example, no edges are printed corresponding to mask edges connecting vertices 1043 to 1045, 1045 to

1046, and 1046 to 1047. Also, the edges of the shifters outside the trim polygon are not printed. For example, the edge connecting vertex 1038 to vertex 1037 is not printed.

Some edges have portions that are printed and portions that are not printed. For example, no edge is printed between points 1043 and 1042 of the polygon 1020 edge connecting points 1043 to 1040. Similarly, no edge is printed between points 1038 and 1042 of shifter 1010a edge connecting point 1038 to point 1031. Such partially printed edges usually involve a point that marks the intersection of a shifter edge with a trim edge, like point 1042.

Figure 10A also illustrates that some portions of some edges are more important than other portions of the same edge, even though both are printed. For example, on shifter edge connecting point 1031 to 1036, the portion making up an edge of the true-gate 1001, between points 1032 and 1035, is more important than other portions of that edge, that simply provide an extension for the connecting features 1009a and 1009b.

According to these embodiments, dissection points and evaluation points are not placed on edges that are not printed, such as outside edges polygons for shifters or edges of trim polygons inside shifters. For example, when dissecting the polygon of shifter 1010a, the edge connecting vertices 1031 and 1036 contains portions that will be printed, therefore this edge is dissected. However, the edge connecting vertices 1037 to 1038 will not be printed; and therefore it is not dissected.

Also according to these embodiments, dissection points and evaluation points are moved or removed to ensure that segments do not have lengths less than a minimum segment length, and that the evaluation points are on the physically important parts of the segments.

According to one embodiment, dissection points are initially placed at the corners of the true-gate, i.e., at points 1032 and 1035 in addition to shifter vertexes 1031 and 1036. The edge of

the true-gate is then dissected as if 1032 and 1035 were vertices of a polygon. For example, normally a dissection point is placed at point 1032 and another dissection point is placed a distance L_{cor} away at 1033, and the evaluation point 1034 is placed two-thirds of the way from point 1032 to point 1033.

5 However, if the length of the resulting segment from vertex 1031 to true-gate corner 1032 is less than the minimum segment length, e.g., the lesser of L_{cor} and L_{det} , a dissection point is not placed at true-gate corner 1032. Instead, the dissection point at 1031 is used. The evaluation point 1034 for the segment remains on the true-gate edge two-thirds of the way between points 1032 and 1033. That is, the evaluation point is located as if the corner of
10 the true-gate 1032 were a corner dissection point. Because the segment from vertex 1031 to point 1032 is used to connect the corner of the shifter to the true-gate, it is referred to as the shifter extension, and the shifter extension length is the distance from shifter vertex 1031 to true gate vertex 1032.

 This technique has the advantage of simultaneously keeping all segment lengths
15 greater than or equal to the minimum segment length, but ensuring that the evaluation points are on the true-gate, the critical feature in the layout. This is an advantage because it is desired that the correction determined at the evaluation point be applicable to the true-gate, which is the important feature. The dissection of an entire edge, like shifter polygon edge from vertex 1031 to 1036, considering the influence of true gate corners is implemented
20 during an alternative embodiment of step 330 of Figure 3.

Where a portion of an edge is not printed, dissection points are selected to avoid segments shorter than the minimum dissection segment length and evaluation points are placed on the portion being printed. According to one embodiment, dissection points are initially placed at the intersection of shifter and trim edges in addition to trim edge vertexes.

For example, a dissection point is initially placed at intersection point 1042 and at point 1041, a distance L_{cor} away. The evaluation point is then placed two-thirds of the way from point 1042 to point 1041, as if the intersection point 1042 were a vertex. However, if the non-printed portion of the edge, from point 1043 to 1042, is shorter than the lesser of L_{cor} and L_{det} , the segment from 1041 to 1042 is extended to point 1043. That is, the segment is extended to the trim 1024a by the trim extension distance from 1042 to 1043. The evaluation point remains unchanged, at two-thirds the distance from the intersection point 1042 to the dissection point 1041. The remaining edge of the polygon 1020 is then dissected according to the rules stated above for non-corner segments.

This technique has the advantage of simultaneously keeping all segment lengths greater than or equal to the minimum segment length, but ensuring that the evaluation points are on the printed portion of the edge. This is an advantage because it is desired that the correction determined at the evaluation point be applicable to the printed edge.

Other arrangements yield other results. For example, Figure 10B shows an arrangement that has one edge of true-gate 1002 formed by a portion of one edge of polygon 1021, between vertices 1054f and 1054g. The true gate corners on this edge are at points 1055a and 1055b. Both of these true-gate corners are also intersections of the shifters 1011 with this edge of the polygon 1021. Whether this edge is further dissected depends on the distance between these corners. If the distance from 1055a to 1055b is less than the minimum segment length, e.g., the lesser of L_{cor} and L_{det} , then this edge of the polygon 1021, between vertices 1054f and 1054g, is not dissected; and no evaluation point is placed on this edge.

If the distance between true-gate corners 1055a and 1055b is greater than or equal to the minimum segment length, then the dissection of this edge of polygon 1021 connecting

vertices 1054f to 1054g proceeds as follows. Normally true-gate corners 1055a and 1055b are dissection points and the evaluation point 1056 is midway between the two, as if the true-gate corners 1055a and 1055b were polygon vertices on a line-end. However, if both edge portions from true-gate corner to edge vertex, i.e. edge portion from vertex 1054f to true-gate corner 1055a and edge portion from true-gate corner 1055b to vertex 1054g, have lengths shorter than the minimum segment length, then the dissection points are moved to the vertices. The evaluation point 1056 remains unchanged, midway between the corners of the true-gate. If only one of these edge portions from true-gate corner to vertex is less than the minimum, the dissection point is moved to the vertex for the short edge portion. For example, if only the edge portion from vertex 1054f to true-gate corner 1055a has a length less than the minimum dissection length, then the dissection point is moved from 1055a to 1054f, while true-gate corner 1055b remains a dissection point. The evaluation point is moved so that it is placed two-thirds of the way from true-gate corner 1055a to 1055b.

These techniques illustrated with respect to Figure 10B offer the advantages of producing no segments that are too short, and producing evaluation points at locations of physical significance even on edges of a polygon that are only partially printed.

Other edges of polygon 1021, such as those connecting vertices 1054b to 1054c, 1054c to 1054d, 1054d to 1054e, and 1054e to 1054f are inside shifter 1011a and are not printed. Also edges of shifters outside the trim, such as edges connecting vertices 1053c to 1053d, 1053d to 1053e, 1053e to 1053f, and 1053f to 1053a are not printed. Therefore these edges of polygon 1021 and shifter 1011 are not dissected. Still other edges, such as that edge of polygon 1021 connecting vertex 1054a to 1054b, are partially printed and are handled as described above with respect to Figure 10A. The edge connecting vertices 1053a and 1053b

of shifter 1011a form corners of the true-gate 1002 as described above with respect to Figure 10A.

In order to print a true-gate area more aggressively, to ensure it will not be underexposed, a true-gate is often artificially extended. The amount that a true-gate is extended during design of a fabrication layout, such as a mask layout, can be specified by a designer with a true-gate extension length parameter L_{ext} . In some instances, the designer may specify several true-gate extension length parameters for different circumstances. For example, a designer may specify a first true-gate extension for use where a true-gate is connected to another element and a second true-gate extension for use where a true-gate is capped by an end-cap.

The actual true-gate extension depends both on the parameters L_{ext} and the actual feature geometries. For example, with respect to Figure 10A, if the distance from true-gate corner 1032 to shifter vertex 1031 is less than L_{ext} , then the true-gate 1001 is extended to the shifter vertex 1031. If, on the other hand, the distance from true-gate corner 1035 to shifter vertex 1036 is greater than L_{ext} , then the true-gate is extended only to point 1039, a distance equal to L_{ext} from the original true-gate corner 1036. According to this example, the true gate 1001 originally lying from point 1032 to point 1035 has been extended on both ends to lie from point 1031 to point 1039.

According to this embodiment, the dissection points are selected to be consistent with the true-gate extension scheme employed in the fabrication layout. For example, the dissection of an edge with a true gate described above is begun after the true-gate is extended to have corners at points 1031 and 1039.

Figure 10C shows shifters 1012 shared across two true-gates 1003 that are not connected to each other. For each true-gate, a polygon 1022 provides a connector 1009 to

other elements, not shown, trim regions 1026, and an end cap 1090. For example, polygon 1022 provides connector 1009d, trim regions 1026a and 1026b, and end cap 1090a.

If Lext parameters have not been defined, then dissection proceeds as follows.

Normally, dissection points are placed at the corners of the true-gate. For example,

- 5 dissections points are placed at 1065a and 1065b for true-gate 1003a, and at 1065c and 1065d for true-gate 1003b. In addition, dissection points are placed a distance Lcor from the corner points of the true-gates. For example, a dissection point is placed at 1063b, a distance Lcor from true-gate corner 1065b, for true-gate 1003a. Similarly, a dissection point is placed at 1063f, a distance Lcor from true-gate corner 1065c, for true-gate 1003b. The evaluation point
10 is placed two-thirds of the way along the resulting segment from the true-gate corner. For example, evaluation point 1066a is placed two-thirds of the way from true-gate corner 1065b to dissection point 1063b. Similarly, evaluation point 1066b is placed two-thirds of the way from true-gate corner 1065c to dissection point 1063f. No evaluation point is placed on the edge portion between the two true-gates, from point 1065b to point 1065c, because that edge
15 is not printed and does not require correction.

- However, if the distance between the true gates is less than the minimum segment length, e.g., the lesser of Lcor and Ldet, then the dissection points are moved to the middle point of the gap. For example, if the distance from true-gate corners 1065b of true-gate 1003a to true-gate corner 1065c of true-gate 1003b is less than the minimum of Lcor and Ldet, then
20 the dissection points at 1065b and 1065c are both moved to point 1063d. The evaluation points are not moved. They remain as if the corners of the true-gate were vertices of the polygon.

If a Lext parameter has been defined, then dissection proceeds as follows. True-gate 1003a is extended to point 1063c, a distance Lext for end caps from the original true-gate

corner at 1065b. Similarly, true-gate 1003b is extended to point 1063e, a distance L_{ext} for end caps from the original true-gate corner at 1065c. No evaluation point is placed on the edge portion between the two true-gates, from point 1063c to point 1063e, because that edge is not printed and does not require correction. Similarly the other corners of the true-gates, 1065a and 1065d are moved outward a distance L_{ext} for connectors to points 1067a and 1067b, respectively. In some embodiments, L_{ext} for end caps is equal to L_{ext} for connectors; in other embodiments they have different values. The evaluation points are placed two-thirds of the way from the extended corners 1063c and 1063e, respectively, to the dissection points 1063b and 1063f, respectively, each dissection point spaced a distance L_{cor} from the extended corners.

However, if the distance between the extended true-gates, from point 1063c to point 1063e, is less than the minimum dissection length, then the dissection points are not placed at 1063c and 1063e, but are both moved to the center point 1063d. The evaluation points are not moved.

The techniques described with respect to Figure 10C have the advantage of defining segments each greater than the minimum segment length for all segments including edges of important features like true-gates. If the entire shared shifter edge is printed, these techniques are implemented during an alternative embodiment of step 330 of Figure 3.

FUNCTIONAL OVERVIEW OF DISSECTING DOUBLY EXPOSED EDGES

Figure 11 illustrates a method for finishing one edge and selecting another edge of a polygon that takes into account whether the edge or a portion of the edge is printed or not. These steps are included in an alternate embodiment 392a of step 392 shown in Figure 3.

In step 1110 it is determined whether all of an edge is important for the edge on which dissection points and evaluation points were most recently selected. If all of the edge

just completed is important, then control passes to step 1120 where the next edge on the polygon is made the current edge. If some of the edge is less important, such as because some of the edge is not a true-gate or some is not printed, then flow passes to step 1115 in which additional dissection points are considered, such as at intersections of polygon edges with shifter edges, and at corners of true gates. Evaluation points are only defined on important portions of segments. After these steps are performed, then flow passes to step 1120 to make the next edge the current edge.

In step 1125 it is determined whether any of the next edge is printed. If not, flow does not return to step 330 (of Figure 3) to select dissection points. Instead, flow passes to step 390 of Figure 3 to determine whether this is the last edge on the current polygon.

If at least some of the edge is printed, flow goes eventually to step 330 to select those dissection points on the next edge.

COMPUTING CORRECTIONS FOR EVALUATION POINTS

Once the dissection points and associated evaluation points are selected, the model is run for the actual layout only for the evaluation points, as shown by process 232 in Figure 2.

The resulting proximity effects model amplitude is used to compute a correction distance

5 during process 234 of Figure 2. The correction distance is then applied to the entire segment between dissection points, moving the segment out or in and creating a new polygon for an adjusted mask layout, as shown by process 236 in Figure 2.

ITERATIVE USE OF PROXIMITY EFFECTS MODEL

Once the segments have been moved by the correction distance for all the affected
10 polygons, the adjusted fabrication layout (produced by process 236 in Figure 2) is completed. This is used as the final fabrication layout 235 in one embodiment. The corrections can be combined with the original polygons to create new flat files of polygons. In the preferred embodiment, a correction is stored as an hierarchical subunit in the hierarchical representation of the original polygon in the initial fabrication layout.

15 In another embodiment, the adjusted fabrication layout 136 is tested again with the proximity effects model to determine whether the agreement between the printed features layer (249 in Figure 2) and the design layout (225 in Figure 2) satisfy a pre-defined specification tolerance. If so, the corrections end. Otherwise, another round of corrections is performed based on the current correction to further improve the agreement. This process
20 iterates until the agreement converges on the specified tolerance for all edges, or it is determined that further improvement is not possible. In this embodiment, the recently adjusted fabrication layout produced during process 236 becomes the next proposed fabrication layout (231) and the processes 260 through 236 are repeated. For example,

dissection points and evaluation points are selected for the new proposed layout, printed features are predicted with the model, and the differences are analyzed.

In one embodiment, only the new edges of the polygon generated by moving certain segments by the corresponding correction distances are dissected. In this embodiment, the halo used to find projection points is also reduced for the next round of evaluations, so that fewer corrections are attempted each round, and the solution can converge. This is accomplished, for example, as shown in Figure 11. Figure 11 shows step 1130, which determines whether the next edge to be processed is a new edge introduced since the last proximity effects model run. An edge will only be new if it includes a segment that was moved as a result of a correction. In step 1130, if the edge is not new, i.e., a segment was not moved, then the edge is skipped. Only new edges have dissection points and evaluation points selected in step 330 of Figure 3.

HARDWARE OVERVIEW

Figure 12 is a block diagram that illustrates a computer system 1200 upon which an embodiment of the invention is implemented. Computer system 1200 includes a bus 1202 or other communication mechanism for communicating information, and a processor 1204 coupled with bus 1202 for processing information. Computer system 1200 also includes a main memory 1206, such as a random access memory (RAM) or other dynamic storage device, coupled to bus 1202 for storing information and instructions to be executed by processor 1204. Main memory 1206 also may be used for storing temporary variables or other intermediate information during execution of instructions to be executed by processor 1204. Computer system 1200 further includes a read only memory (ROM) 1208 or other static storage device coupled to bus 1202 for storing static information and instructions for processor 1204. A storage device 1210, such as a magnetic disk or optical disk, is provided and coupled to bus 1202 for storing information and instructions.

Computer system 1200 may be coupled via bus 1202 to a display 1212, such as a cathode ray tube (CRT), for displaying information to a computer user. An input device 1214, including alphanumeric and other keys, is coupled to bus 1202 for communicating information and command selections to processor 1204. Another type of user input device is cursor control
5 1216, such as a mouse, a trackball, or cursor direction keys for communicating direction information and command selections to processor 1204 and for controlling cursor movement on display 1212. This input device typically has two degrees of freedom in two axes, a first axis (e.g., x) and a second axis (e.g., y), that allows the device to specify positions in a plane.

The invention is related to the use of computer system 1200 for producing design
10 layouts and fabrication layouts. According to one embodiment of the invention, dissection points and evaluation points for fabrication layouts are provided by computer system 1200 in response to processor 1204 executing, e.g., as threads, one or more sequences of one or more instructions contained in main memory 1206. For example, the evaluation point determining process runs as a thread 1252 on processor 1204 based on evaluation point determining
15 process instructions 1251 stored in main memory 1206. Such instructions may be read into main memory 1206 from another computer-readable medium, such as storage device 1210. Execution of the sequences of instructions contained in main memory 1206 causes processor 1204 to perform the process steps described herein. In alternative embodiments, hard-wired circuitry may be used in place of or in combination with software instructions to implement
20 the invention. Thus, embodiments of the invention are not limited to any specific combination of hardware circuitry and software.

The term "computer-readable medium" as used herein refers to any medium that participates in providing instructions to processor 1204 for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and
25 transmission media. Non-volatile media includes, for example, optical or magnetic disks, such as storage device 1210. Volatile media includes dynamic memory, such as main memory 1206. Transmission media includes coaxial cables, copper wire and fiber optics, including the

wires that comprise bus 1202. Transmission media can also take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.

Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, punchcards, papertape, any other physical medium with patterns of holes, a RAM, a PROM, and EPROM, a FLASH-EPROM, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read.

Various forms of computer readable media may be involved in carrying one or more sequences of one or more instructions to processor 1204 for execution. For example, the instructions may initially be carried on a magnetic disk of a remote computer. The remote computer can load the instructions into its dynamic memory and send the instructions over a telephone line using a modem. A modem local to computer system 1200 can receive the data on the telephone line and use an infra-red transmitter to convert the data to an infra-red signal. An infra-red detector can receive the data carried in the infra-red signal and appropriate circuitry can place the data on bus 1202. Bus 1202 carries the data to main memory 1206, from which processor 1204 retrieves and executes the instructions. The instructions received by main memory 1206 may optionally be stored on storage device 1210 either before or after execution by processor 1204.

Computer system 1200 also includes a communication interface 1218 coupled to bus 1202. Communication interface 1218 provides a two-way data communication coupling to a network link 1220 that is connected to a local network 1222. For example, communication interface 1218 may be an integrated services digital network (ISDN) card or a modem to provide a data communication connection to a corresponding type of telephone line. As another example, communication interface 1218 may be a local area network (LAN) card to provide a data communication connection to a compatible LAN. Wireless links may also be implemented. In any such implementation, communication interface 1218 sends and

receives electrical, electromagnetic or optical signals that carry digital data streams representing various types of information.

Network link 1220 typically provides data communication through one or more networks to other data devices. For example, network link 1220 may provide a connection through local network 1222 to a host computer 1224. Local network 1222 uses electrical, electromagnetic or optical signals that carry digital data streams. The signals through the various networks and the signals on network link 1220 and through communication interface 1218, which carry the digital data to and from computer system 1200, are exemplary forms of carrier waves transporting the information.

Computer system 1200 can send messages and receive data, including program code, through the network(s), network link 1220 and communication interface 1218.

The received code may be executed by processor 1204 as it is received, and/or stored in storage device 1210, or other non-volatile storage for later execution. In this manner, computer system 1200 may obtain application code in the form of a carrier wave.

In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

CLAIMS

What is claimed is:

1. A method of correcting for proximity effects in a proposed layout corresponding to a design layout for a printed features layer, the method comprising:
 - selecting from among all edges of all polygons in the proposed layout a subset of edges for which proximity corrections are desirable, wherein the subset of edges includes less than said all edges;
 - establishing evaluation points only for the subset of edges; and
 - determining corrections for at least portions of the subset of edges based on an analysis performed at the evaluation points.
2. The method of claim 1 said selecting further comprising:
 - determining if a correction for an edge among all edges was non-zero during a previous round of said determining corrections; and
 - if the correction was non-zero, then adding the edge to the subset of edges.
3. The method of claim 1 said selecting further comprising:
 - determining if a correction for a second edge within a halo distance of a first edge was non-zero during a previous round of said determining corrections; and
 - if the correction was non-zero, then adding the first edge to the subset of edges.
4. The method of claim 1 said selecting further comprising:
 - determining if an edge corresponds to a critical feature in the proposed layout with a dimension close to a resolution of a fabrication process for the printed features layer; and
 - if the edge corresponds to a critical feature, then adding the edge to the subset of edges.

1 5. A method of using a computer to correct a proposed layout for proximity effects, said
2 layout corresponding to a design layout, the computer having a processor coupled to a
3 computer-readable medium, the computer-readable medium storing at least a portion of the
4 design layout, the design layout corresponding to a portion of an integrated circuit, the
5 method comprising:

6 selecting from among all edges of all polygons in the proposed layout a subset of
7 edges for which proximity corrections are desirable, wherein the subset of
8 edges includes less than said all edges;
9 establishing evaluation points only for the subset of edges in the proposed layout; and
10 determining corrections for at least portions of the subset of edges based on an
11 analysis performed at the evaluation points.

1 6. The method of claim 5 said selecting further comprising:
2 determining if a correction for an edge among all edges was non-zero during a
3 previous round of said determining corrections; and
4 if the correction was non-zero, then adding the edge to the subset of edges.

1 7. The method of claim 5 said selecting further comprising:
2 determining if a correction for a second edge within a halo distance of a first edge
3 was non-zero during a previous round of said determining corrections; and
4 if the correction was non-zero, then adding the first edge to the subset of edges.

1 8. The method of claim 5 said selecting further comprising:
2 determining if an edge corresponds to a critical feature in the proposed layout with a
3 dimension close to a resolution of a fabrication process for the printed features
4 layer; and
5 if the edge corresponds to a critical feature, then adding the edge to the subset of
6 edges.

1 9. A method of correcting for proximity effects associated with an edge corresponding
2 to a design layout, the method comprising:
3 establishing a projection point on a first edge corresponding to the design layout
4 based on whether a vertex of a second edge corresponding to the design layout
5 is within a halo distance of the first edge, wherein the halo distance is
6 associated with significant proximity effects on one edge from a vertex of
7 another edge;
8 dividing the first edge into segments based on the projection point and characteristics
9 of the first edge; and
10 determining how to correct the first edge for proximity effects based on the segments.

1 10. The method of claim 9, said establishing a projection point further comprising, if the
2 vertex of the second edge is within the halo distance of the first edge, then placing the
3 projection point on the first edge substantially closest to the vertex.

1 11. The method of claim 9, wherein the halo distance is based on one or more profiles of
2 amplitudes output by a proximity effects model.

1 12. The method of claim 9, said dividing the edge into segments further based on a target
2 length for detail segments.

1 13. The method of claim 12, said dividing the first edge into segments further comprising
2 establishing a segment on the first edge including the projection point and having a length no
3 less than the target length for detail segments.

1 14. The method of claim 13, wherein the length of the segment on the first edge is
2 substantially equal to the target length for detail segments.

1 15. The method of claim 12, wherein the target length for detail segments is based on one
2 or more profiles of amplitudes output by a proximity effects model.

1 16. The method of claim 12, said dividing the first edge into segments further comprising
2 establishing two segments on the first edge, the two segments meeting substantially at the
3 projection point, each segment having a length no less than the target length for detail
4 segments.

1 17. The method of claim 12, said dividing the first edge into segments further comprising
2 establishing three segments on the first edge, wherein:

3 a first segment includes the projection point and has a length equal to the target length
4 for detail segments; and
5 two other segments are each adjacent to the first segment and have lengths no less
6 than the target length for detail segments.

1 18. The method of claim 9, before said establishing a projection point, further comprising
2 determining the halo distance.

1 19. The method of claim 18, said determining the halo distance further comprising
2 receiving from a user at least one of the halo distance and a fraction of a model radius,
3 wherein:

4 the model radius indicates a greatest distance influencing a point according to a
5 proximity effects model; and
6 the fraction is less than one.

1 20. The method of claim 18, said determining the halo distance further comprising
2 reducing a previous halo distance used during a previous round of corrections.
3

3

1 21. The method of claim 18, said determining the halo distance further comprising:
2 executing a routine implementing a proximity effects model at a plurality of points
3 along a test edge to produce a profile of model amplitudes;
4 determining a variation in amplitude associated with a test vertex on a different test
5 edge;
6 associating a distance between the test edge and the test vertex with the variation in
7 amplitude;
8 repeating for a plurality of test edges said executing the routine, said determining the
9 variation, and said associating the distance; and
10 setting the halo distance based on a distribution of distances associated with
11 variations for the plurality of test edges.

1 22. The method of claim 21, said setting the halo distance further comprising:
2 determining a particular distance in the distribution of distances associated with a
3 certain change in amplitude; and
4 setting the halo distance based on the particular distance.

1 23. The method of claim 22, wherein the certain change in amplitude is associated with a
2 certain percentile of the variations for the plurality of test edges.

1 24. The method of claim 22, wherein the particular distance is a greatest distance
2 associated with the certain change in amplitude in the distribution.

1 25. A method of using a computer to correct for proximity effects associated with an edge
2 corresponding to a design layout, the computer having a processor coupled to a computer-
3 readable medium, the computer-readable medium storing at least a portion of the design

layout, the design layout corresponding to a portion of an integrated circuit, the method comprising:

establishing a projection point on a first edge corresponding to the design layout based on whether a vertex of a second edge corresponding to the design layout is within a halo distance of the first edge, wherein the halo distance is associated with significant proximity effects on one edge from a vertex of another edge;

dividing the edge into segments based on the projection point and the characteristics of the edge; and

determining how to correct the edge for proximity effects based on the segments.

26. A method of correcting for proximity effects associated with an edge corresponding to a design layout, the method comprising:

establishing a projection point on a first edge corresponding to the design layout based on whether a vertex of a second edge corresponding to the design layout is within a halo distance of the first edge, wherein the halo distance is associated with significant proximity effects on one edge from a vertex of another edge;

determining an evaluation point for the first edge based on the projection point and characteristics of the first edge; and

determining how to correct at least a portion of the edge for proximity effects based on an analysis at the evaluation point.

27. The method of claim 26, said establishing a projection point further comprising, if the vertex of the second edge is within the halo distance of the first edge, then placing the projection point on the first edge substantially closest to the vertex.

1 28. The method of claim 26, wherein the halo distance is based on one or more profiles of
2 amplitudes output by a proximity effects model.

1 29. The method of claim 26, said determining the evaluation point further comprising
2 establishing the evaluation point on the first edge at the projection point.

1 30. The method of claim 26, said determining the evaluation point further based on a
2 target length for detail segments.

1 31. The method of claim 30, said determining the evaluation point further comprising
2 establishing on the first edge two evaluation points spaced apart at least by the target length
3 for detail segments and straddling the projection point.

1 32. The method of claim 31, wherein the two evaluation points are spaced apart by the
2 target length for detail segments.

1 33. The method of claim 31, wherein the projection point is substantially midway
2 between the two evaluation points.

1 34. The method of claim 30, said determining the evaluation point further comprising
2 establishing on the first edge three evaluation points spaced apart at least by the target length
3 for detail segments, wherein:

4 a first evaluation point is placed substantially at the projection point; and
5 two other evaluation points are placed on opposite sides of the first evaluation point.

1 35. The method of claim 26, before said establishing a projection point, further
2 comprising determining the halo distance.

1 36. The method of claim 35, said determining the halo distance further comprising
2 receiving from a user at least one of the halo distance and a fraction of a model radius,
3 wherein:

4 the model radius indicates a greatest distance influencing a point according to a
5 proximity effects model; and
6 the fraction is less than one.

1 37. The method of claim 35, said determining the halo distance further comprising
2 reducing a previous halo distance used during a previous round of corrections.

1 38. The method of claim 35, said determining the halo distance further comprising:
2 executing a routine implementing a proximity effects model at a plurality of points
3 along a test edge to produce a profile of model amplitudes;
4 determining a variation in amplitude associated with a test vertex on a different test
5 edge;
6 associating a distance between the test edge and the test vertex with the variation in
7 amplitude;
8 repeating for a plurality of test edges said executing the routine, said determining the
9 variation, and said associating the distance; and
10 setting the halo distance based on a distribution of distances associated with
11 variations for the plurality of test edges.

1 39. The method of claim 38, said setting the halo distance further comprising:
2 determining a particular distance in the distribution of distances associated with a
3 certain change in amplitude; and
4 setting the halo distance based on the particular distance.

1 40. The method of claim 39, wherein the certain change in amplitude is associated with a
2 certain percentile of the variations for the plurality of test edges.

1 41. The method of claim 39, wherein the particular distance is a greatest distance
2 associated with the certain change in amplitude in the distribution.

1 42. A method of using a computer to correct for proximity effects associated with an edge
2 corresponding to a design layout, the computer having a processor coupled to a computer-
3 readable medium, the computer-readable medium storing at least a portion of the design
4 layout, the design layout corresponding to a portion of an integrated circuit, the method
5 comprising:

6 establishing a projection point on a first edge corresponding to the design layout
7 based on whether a vertex of a second edge corresponding to the design layout
8 is within a halo distance of the first edge, wherein the halo distance is
9 associated with significant proximity effects on one edge from a vertex of
10 another edge;
11 determining an evaluation point for the edge based on the projection point and the
12 characteristics of the first edge; and
13 determining how to correct at least a portion of the edge for proximity effects based
14 on an analysis at the evaluation point.

1 43. A computer readable medium for correcting proximity effects in a proposed layout
2 corresponding to a design layout for a printed features layer, the computer readable medium
3 carrying instructions to cause one or more processors to perform:

4 selecting from among all edges of all polygons in the proposed layout a subset of
5 edges for which proximity corrections are desirable, wherein the subset of
6 edges includes less than said all edges;
7 establishing evaluation points only for the subset of edges; and

determining corrections for at least portions of the subset of edges based on an analysis performed at the evaluation points.

44. A computer readable medium for correcting proximity effects associated with an edge corresponding to a design layout, the computer readable medium carrying instructions to cause one or more processors to perform:

establishing a projection point on a first edge corresponding to the design layout based on whether a vertex of a second edge corresponding to the design layout is within a halo distance of the first edge, wherein the halo distance is associated with significant proximity effects on one edge from a vertex of another edge;
dividing the first edge into segments based on the projection point and characteristics of the first edge; and
determining how to correct the first edge for proximity effects based on the segments.

45. A computer readable medium for correcting proximity effects associated with an edge corresponding to a design layout, the computer readable medium carrying instructions to cause one or more processors to perform:

establishing a projection point on a first edge corresponding to the design layout based on whether a vertex of a second edge corresponding to the design layout is within a halo distance of the first edge, wherein the halo distance is associated with significant proximity effects on one edge from a vertex of another edge;
determining an evaluation point for the first edge based on the projection point and characteristics of the first edge; and
determining how to correct at least a portion of the edge for proximity effects based on an analysis at the evaluation point.

1 46. A carrier wave for correcting proximity effects in a proposed layout corresponding to
2 a design layout for a printed features layer, the carrier wave carrying instructions to cause
3 one or more processors to perform:

4 selecting from among all edges of all polygons in the proposed layout a subset of
5 edges for which proximity corrections are desirable, wherein the subset of
6 edges includes less than said all edges;

7 establishing evaluation points only for the subset of edges; and

8 determining corrections for at least portions of the subset of edges based on an
9 analysis performed at the evaluation points.

1 47. A carrier wave for correcting proximity effects associated with an edge corresponding
2 to a design layout, the carrier wave carrying instructions to cause one or more processors to
3 perform:

4 establishing a projection point on a first edge corresponding to the design layout
5 based on whether a vertex of a second edge corresponding to the design layout
6 is within a halo distance of the first edge, wherein the halo distance is
7 associated with significant proximity effects on one edge from a vertex of
8 another edge;

9 dividing the first edge into segments based on the projection point and characteristics
10 of the first edge; and

11 determining how to correct the first edge for proximity effects based on the segments.

1 48. A carrier wave for correcting proximity effects associated with an edge corresponding
2 to a design layout, the carrier wave carrying instructions to cause one or more processors to
3 perform:

4 establishing a projection point on a first edge corresponding to the design layout

5 based on whether a vertex of a second edge corresponding to the design layout

is within a halo distance of the first edge, wherein the halo distance is associated with significant proximity effects on one edge from a vertex of another edge;

determining an evaluation point for the first edge based on the projection point and characteristics of the first edge; and
determining how to correct at least a portion of the edge for proximity effects based on an analysis at the evaluation point.

49. A computer system for correcting a proposed layout corresponding to a design layout for proximity effects, the computer system comprising:

a computer readable medium carrying data representing the edge and at least a portion of the design layout, the design layout corresponding to a portion of an integrated circuit; and
one or more processors coupled to the computer readable medium, the one or more processors configured for
selecting from among all edges of all polygons in the proposed layout a subset of edges for which proximity corrections are desirable, wherein the subset of edges includes less than said all edges;
establishing evaluation points only for the subset of edges; and
executing a routine implementing a proximity effects model for the evaluation points to produce model amplitudes,
determining corrections for the evaluation points based on an analysis of the model amplitudes, and
applying the corrections to at least portions of the edges including the evaluation points.

50. A computer system for correcting proximity effects associated with an edge corresponding to a design layout, the computer system comprising:

3 a computer readable medium carrying data representing the edge, a halo distance
4 associated with significant proximity effects on one edge from a vertex of
5 another edge, and at least a portion of the design layout, the design layout
6 corresponding to a portion of an integrated circuit; and
7 one or more processors coupled to the computer readable medium, the one or more
8 processors configured for
9 establishing a projection point on a first edge corresponding to the design
10 layout based on whether a vertex of a second edge corresponding to
11 the design layout is within the halo distance of the first edge;
12 dividing the first edge into segments based on the projection point and
13 characteristics of the first edge;
14 executing a routine implementing a proximity effects model for evaluation
15 points on the segments to produce model amplitudes for the evaluation
16 points,
17 determining corrections for the segments based on an analysis of the model
18 amplitudes, and
19 applying the corrections to the segments.

1 51. A computer system for correcting proximity effects associated with an edge
2 corresponding to a design layout, the computer system comprising:
3 a computer readable medium carrying data representing the edge, a halo distance
4 associated with significant proximity effects on one edge from a vertex of
5 another edge, and at least a portion of the design layout, the design layout
6 corresponding to a portion of an integrated circuit; and
7 one or more processors coupled to the computer readable medium, the one or more
8 processors configured for

9 establishing a projection point on a first edge corresponding to the design
10 layout based on whether a vertex of a second edge corresponding to
11 the design layout is within the halo distance of the first edge;
12 determining an evaluation point for the first edge based on the projection point
13 and characteristics of the first edge; and
14 executing a routine implementing a proximity effects model for the evaluation
15 point to produce a model amplitude,
16 determining a correction for at least a portion of the first edge including the
17 evaluation point based on an analysis of the model amplitude, and
18 applying the correction to the portion of the first edge.

0962549 "0962549"
1 52. A system for correcting proximity effects in a proposed layout corresponding to a
2 design layout for a printed features layer, the system comprising:
3 a means for selecting from among all edges of all polygons in the proposed layout a
4 subset of edges for which proximity corrections are desirable, wherein the
5 subset of edges includes less than said all edges;
6 a means for establishing evaluation points only for the subset of edges;
7 a proximity effects model for producing model amplitudes at the evaluation points;
8 a means for analyzing the model amplitudes to determine corrections at the evaluation
9 points; and
10 a means for applying the corrections to at least portions of the subset of edges.

1 53. A system for correcting proximity effects associated with an edge corresponding to a
2 design layout, the system comprising:

3 a means for establishing a projection point on a first edge corresponding to the design
4 layout based on whether a vertex of a second edge corresponding to the design
5 layout is within a halo distance of the first edge, wherein the halo distance is
6 associated with significant proximity effects on one edge from a vertex of
7 another edge;

8 a means for dividing the first edge into segments based on the projection point and
9 characteristics of the first edge;

10 a proximity effects model for producing model amplitudes at evaluation points on the
11 segments;

12 a means for analyzing the model amplitudes to determine corrections for the
13 segments; and

14 a means for applying the corrections to the segments.

1 54. A system for correcting proximity effects associated with an edge corresponding to a
2 design layout, the system comprising:

3 a means for establishing a projection point on a first edge corresponding to the design
4 layout based on whether a vertex of a second edge corresponding to the design
5 layout is within a halo distance of the first edge, wherein the halo distance is
6 associated with significant proximity effects on one edge from a vertex of
7 another edge;

8 a means for determining an evaluation point for the first edge based on the projection
9 point and characteristics of the first edge,

10 a proximity effects model for producing a model amplitude at the evaluation point;

11 a means for analyzing the model amplitude to determine a correction at the evaluation
12 point; and

13 a means for applying the correction to at least a portion of the first edge including the
14 evaluation point.

1 55. A method for fabricating a printed features layer including features corrected for
2 proximity effects, the method comprising:
3 building an initial fabrication layout based on a design layout corresponding to the
4 printed features layer;
5 selecting from among all edges of all polygons in the initial fabrication layout a
6 subset of edges for which proximity corrections are desirable, wherein the
7 subset of edges includes less than said all edges;
8 establishing evaluation points only for the subset of edges;
9 executing a routine implementing a proximity effects model for producing model
10 amplitudes at the evaluation points;
11 analyzing the model amplitudes to determine corrections at the evaluation points;
12 applying the corrections to at least portions of the subset of edges;
13 producing a mask based on the corrected subset of edges; and
14 producing the printed features layer in a fabrication process using the mask.

1 56. A method for fabricating a printed features layer including features corrected for
2 proximity effects, the method comprising:
3 building an initial fabrication layout based on a design layout corresponding to the
4 printed features layer;
5 establishing a projection point on a first edge corresponding to the design layout
6 based on whether a vertex of a second edge corresponding to the design layout
7 is within a halo distance of the first edge, wherein the halo distance is
8 associated with significant proximity effects on one edge from a vertex of
9 another edge;

dividing the first edge into segments based on the projection point and characteristics
of the first edge;
executing a routine implementing a proximity effects model for producing model
amplitudes at evaluation points on the segments;
analyzing the model amplitudes to determine corrections for the segments;
applying the corrections to the segments in an adjusted fabrication layout;
producing a mask based on the adjusted fabrication layout; and
producing the printed features layer in a fabrication process using the mask.

57. A method for fabricating a printed features layer including features corrected for
proximity effects, the method comprising:
building an initial fabrication layout based on a design layout corresponding to the
printed features layer;
establishing a projection point on a first edge corresponding to the design layout
based on whether a vertex of a second edge corresponding to the design layout
is within a halo distance of the first edge, wherein the halo distance is
associated with significant proximity effects on one edge from a vertex of
another edge;
determining an evaluation point for the first edge based on the projection point and
characteristics of the first edge;
executing a routine implementing a proximity effects model for producing a model
amplitude at the evaluation point;
analyzing the model amplitude to determine a correction at the evaluation point;
applying the correction to at least a portion of the edge including the evaluation point
in an adjusted fabrication layout;
producing a mask based on the adjusted fabrication layout; and
producing the printed features layer in a fabrication process using the mask.

1 58. A mask for fabricating a printed features layer, the mask including an opaque region
2 having segments corrected for proximity effects, the segments corresponding to portions of
3 an edge in a design layer for the printed features layer, wherein:
4 the segments are displaced from the corresponding portions in the design layer by
5 correction distances;
6 the segments correspond to a subset of edges including less than all edges in the
7 design layer, wherein proximity corrections are determined to be desirable for
8 the subset;
9 the correction distances are based on analysis of amplitudes output by a proximity
10 effects model at evaluation points on the corresponding portions of only the
11 subset of edges.

1 59. A mask for fabricating a printed features layer, the mask including an opaque region
2 having segments corrected for proximity effects, the segments corresponding to portions of a
3 first edge in a design layer for the printed features layer, wherein:
4 the segments are displaced from the corresponding portions in the design layer by
5 correction distances;
6 the correction distances are based on analysis of amplitudes output by a proximity
7 effects model at evaluation points on the corresponding portions;
8 the corresponding portions of the edge are based on a projection point and
9 characteristics of the edge; and
10 the projection point is established based on whether a vertex of a second edge
11 corresponding to the design layout is within a halo distance of the first edge,
12 wherein the halo distance is associated with significant proximity effects on
13 one edge from a vertex of another edge.

60. A mask for fabricating a printed features layer, the mask including an opaque region having a segment corrected for proximity effects, the segment corresponding to at least one portion of a first edge in a design layer for the printed features layer, wherein:

the segment is displaced from the corresponding portion in the design layer by a correction distance;

the correction distance is based on analysis of an amplitude output by a proximity effects model at an evaluation point on the corresponding portion;

the evaluation point is based on a projection point and characteristics of the edge; and

the projection point is established based on whether a vertex of a second edge

corresponding to the design layout is within a halo distance of the first edge,

wherein the halo distance is associated with significant proximity effects on

one edge from a vertex of another edge.

61. A device having a proximity-corrected element, the device produced using a mask including an opaque region having segments corrected for proximity effects, the segments corresponding to portions of an edge in a design layer for the printed features layer, wherein:

the segments are displaced from the corresponding portions in the design layer by correction distances;

the segments correspond to a subset of edges including less than all edges in the

design layer, wherein proximity corrections are determined to be desirable for the subset;

the correction distances are based on analysis of amplitudes output by a proximity

effects model at evaluation points on the corresponding portions of only the

subset of edges.

62. A device having a proximity-corrected element, the device produced using a mask including an opaque region having segments corrected for proximity effects, the segments

corresponding to portions of a first edge in a design layer for the printed features layer,
wherein:

the segments are displaced from the corresponding portions in the design layer by
correction distances;

the correction distances are based on analysis of amplitudes output by a proximity
effects model at evaluation points on the corresponding portions;

the corresponding portions of the edge are based on a projection point and
characteristics of the edge; and

the projection point is established based on whether a vertex of a second edge
corresponding to the design layout is within a halo distance of the first edge,
wherein the halo distance is associated with significant proximity effects on
one edge from a vertex of another edge.

63. A device having a proximity-corrected element, the device produced using a mask
including an opaque region having a segment corrected for proximity effects, the segment
corresponding to at least one portion of a first edge in a design layer for the printed features
layer, wherein:

the segment is displaced from the corresponding portion in the design layer by a
correction distance;

the correction distance is based on analysis of an amplitude output by a proximity
effects model at an evaluation point on the corresponding portion;

the evaluation point is based on a projection point and characteristics of the edge; and
the projection point is established based on whether a vertex of a second edge

corresponding to the design layout is within a halo distance of the first edge,
wherein the halo distance is associated with significant proximity effects on
one edge from a vertex of another edge.

ABSTRACT OF THE DISCLOSURE

Techniques for fabricating a device include forming a fabrication layout, such as a mask layout, for a physical design layer, such as a design for an integrated circuit, and identifying evaluation points on an edge of a polygon corresponding to the design layer for correcting proximity effects. Techniques include selecting from among all edges of all polygons in a proposed layout a subset of edges for which proximity corrections are desirable. The subset of edges includes less than all the edges. Evaluation points are established only for the subset of edges. Corrections are determined for at least portions of the subset of edges based on an analysis performed at the evaluation points. Other techniques include establishing a projection point on a first edge corresponding to the design layout based on whether a vertex of a second edge is within a halo distance. An evaluation point is determined for the first edge based on the projection point and characteristics of the first edge. It is then determined how to correct at least a portion of the edge for proximity effects based on an analysis at the evaluation point.




Figure 1A




Figure 1B




Figure 2




Figure 3




Figure 4A




Figure 4B




Figure 4C




Figure 4D




FIGURE 5A




FIGURE 5B




FIGURE 5C




FIGURE 5D




Figure 6








Figure 7






Figure 8E




Figure 9A




Figure 9B

FIGURE 10A





FIGURE 10B






FIGURE 10C





Figure 11

Figure 12



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought on the **PROXIMITY MODEL DISSECTION FOR PROJECTION POINTS**, the specification of which

☒ is attached hereto.

☐ was filed on _____ as Application Serial No. _____ and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is known to me to be material to patentability in accordance with Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Applications(s):

Number	Country	Day/Month/Year filed	Priority Claimed
			<input type="checkbox"/>
			<input type="checkbox"/>

I hereby claim the benefit under 35 USC §119(e) of any United States provisional application(s) listed below.

Prior Provisional Application(s):

Filing Date:

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. Application(s):

Serial No.	Filing Date	Status: Patented, Pending, Abandoned
------------	-------------	--------------------------------------


I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorney(s) and/or agent(s): Edward A. Becker, Reg. No. 37,777; Marcel K. Bingham, Reg. No. 42,327; Carl L. Brandt, Reg. No. 44,555; Brian D. Hickman, Reg. No. 35,894; Craig G. Holmes, Reg. No. 44,770; Christopher J. Palermo, Reg. No. 42,056; Carina M. Tan, Reg. No. 45,769; and Bobby K. Truong, Reg. No. 37,499, all of

HICKMAN PALERMO TRUONG & BECKER LLP
1600 Willow Street
San Jose, CA 95125-5106

with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and all future correspondence should be addressed to them.

Full name of sole or first inventor: CHRISTOPHE PIERRAT

Inventor's signature: 

Date:


9/26/00

Residence: 420 Riverside Court, Apt. 307, Santa Clara, CA 95054

Citizenship: France

Post Office Address: 420 Riverside Court, Apt. 307, Santa Cruz, CA 95054

Full name of second inventor: YOUPIING ZHANG

Inventor's signature: 

Date:

9/29/00

Residence: 37151 Magnolia Street, Newark, CA 94560

Citizenship: Republic of China

Post Office Address: